

Eureka Interlocking Rubber Tiles Specifications

Tile Size:	23 x 23 inches x 8 mm
Tile Weight:	7.7 lbs.
Material:	Vinyl on plastic
Colors:	Black, 10% color fleck, 10% Premium color fleck, 20% color fleck, Team colors fleck
Texture:	Smooth
Coverage:	3.67 square feet per tile
Weight Loading:	Human foot traffic, exercise machines, barbells, weights
Surfaces Install:	Flat hard surface, indoor
Shipping:	9 piece per carton, 20 cartons per standard 4x4 ft pallet
Features:	<ol style="list-style-type: none">1) Interlocking tiles2) Slip resistant3) Can be cut to fit4) Easy to clean5) Easy puzzle tile installation6) Waterproof and non-slip7) Use for home and professional gyms, locker rooms, doggy day care
Product Testing:	<ol style="list-style-type: none">a. Static Load, 1000 lb/in² (ASTM F970): less than 0.020 in.d. Coefficient of Friction (ASTM 2047): greater than 0.9.e. Chemical Resistance (ASTM F925):<ol style="list-style-type: none">1. 5% Acetic Acid: No Change2. 70% Isopropyl Alcohol: No Change3. 5% Sodium Hydroxide: No Change4. 5% Hydrochloric Acid: No Change5. 5% Ammonia: No Change6. Bleach: No Change7. 5% Phenol: No Change8. Sulfuric Acid: No Changef. Ambient Noise Reduction, Sabin/ft² (ASTM C423): 0.10.g. Impact Insulation Class (ASTM E492): 53 minimum.h. Sound Transmission Coefficient (ASTM E90): 54 Minimumi. Delta IIC (ASTM E2179): 22j. Force Reduction (Deltec): 10.4%k. Energy Restitution (Deltec): 71.9%

Eureka Interlocking Rubber Tiles Specifications - continued

- l. Tensile Strength (ASTM D412): 200 psi min
- m. Flexibility ¼" Mandrel (ASTM F137): Pass
- n. Thermal Resistance "R": ASTM (C518)
- o. Color Stability (ASTM F1515): Good
- p. Abrasion Resistance (ASTM D3389): <1g, 100 cycles
- q. Flammability (ASTM D2859): Pass
- r. CHPS/CA 01350 (ASTM D5116):
- s. VOC Washington State IAQ Test (ASTM D5116):
- t. Sustainability (ASTM E 2129): Recorded

Warranty:

5 year limited

Greatmats.com
117 Industrial Ave
Milltown, WI 54858
Toll free: 877-822-6622
Direct voice: 715-653-6100
info@greatmats.com
Revised 11/2023