



## Performance Monster Rubber Roll Product Specifications

Skus: Perf-M-22.5

Roll Size: 4' wide + 3/4" – 0", by custom length, + 1% - 0". Minimum length 30 LF.

Roll Thickness: 22 mm: 12mm Base Layer, installed under 8mm recycled rubber, fusion bonded to 2.5 mm Surface Wear Layer, +/- .6mm

Roll Weight: 4.1 lbs per sf

Colors: Blue Premium, Dark Gray Premium, Mocha Latte, Steel Appeal

Material: High quality post-consumer recycled rubber granules encapsulated in a wear and water-resistant elastomeric network with a fusion bonded reprocessed EPDM surface wear layer.

Performance Criteria	Test Method	Result
Tensile Strength	ASTM D 412	200 PSI min
Flexibility ¼" mandrel	ASTM F 137	Pass
Thermal Conductivity	ASTM C 518	1.3 Btu-in/h-ft-F
Static Load Limit	ASTM F 970 @ 250PSI	0.025"
Coefficient of Friction	ASTM D 2047	> 0.8
V.O.C. Compliant	ASTM D 5116	Yes
Color Stability	ASTM F-1515	Δ E <8.0
Chemical Resistance	ASTM F-925	Pass
Abrasion Resistance	ASTM D 3389 / EN 649	<1g, 100 cycle
Resistance to Heat	ASTM F 1514	Δ E <8.0
Pill Test	ASTM D 2859	Pass
Vertical Deflection / Deformation	ASTM F 2772	1.6 mm Pass
Surface Effect Slip Resistance	ASTM F 2772	Pass
Ball Rebound	ASTM F 2772	100%
Force Reduction	ASTM F 2772	40%

Surfaces Install: Flat Hard Surface, Indoors

Shipping: Shrink wrapped on pallets, ships via freight delivery.

Greatmats.com  
117 Industrial Ave  
Milltown, WI 54858  
Toll free: 877-822-6622  
Fax: 715-825-4928  
info@greatmats.com  
11/2016