

Product Specifications For EZ Floor Underlayment SKU #612089-5

Product Description: Agglomerated recycled high density foam granule underlayment with integrated moisture barrier for impact noise reduction and subfloor preparation with luxury vinyl flooring.

Material: Foam

Roll Size: 42 inches x 49.24 feet x 5 mm

Roll Weight: 80 lbs

Density: 29-33 lb / ft

Tensile Strength: > 800 KPa / 100 PSI

Compression: @ 100 psi: <20%

Recovery: > 85% Minimum

Shore Hardness: 55

PERM rating: = / < 0.3

Environmental Properties: Recycled content (LEED – MR 4), 80% + recycled content by weight

Acoustical Results: ASTM E492/E989: IIC 69 - 6" Concrete Slab – drywall ceiling
ASTM 2179: Delta ICC Rating – 20
ASTM E90 / E413: STC 66 – 6" Concrete slab – drywall ceiling

Shipping: Shrink wrapped on pallets, 12 rolls per pallet

Features:

- a) Integrated moisture vapor barrier
- b) Hides minor subfloor defects
- c) Improves walking comfort under foot
- d) Non-absorbent, resists mold & mildew
- e) Thermal comfort, floors feel warmer

Warranty: 10 Year residential warranty

Greatmats.com
117 Industrial Ave
Milltown, WI 54858
V: 877-822-6622
F: 715-825-4928
info@greatmats.com
revised 5/2017