

### Product Specifications For EZ Floor Underlayment SKU #612089

**Product Description:** Agglomerated recycled high density foam granule underlayment with integrated moisture barrier for impact noise reduction and subfloor preparation with luxury vinyl flooring.

**Material:** Foam

**Roll Size:** 42 inches x 49.24 feet x 2 mm

**Roll Weight:** 37 lbs

**Density:** 29-33 lb / ft

**Tensile Strength:** > 800 KPa / 100 PSI

**Compression:** @ 100 psi: <20%

**Recovery:** > 85% Minimum

**Shore Hardness:** 55

**PERM rating:** = / < 0.3

**Environmental Properties:** Recycled content (LEED – MR 4), 80% + recycled content by weight

**Acoustical Results:** ASTM E492/E989: IIC 69 - 6" Concrete Slab – drywall ceiling  
ASTM 2179: Delta ICC Rating – 20  
ASTM E90 / E413: STC 66 – 6" Concrete slab – drywall ceiling

**Shipping:** Shrink wrapped on pallets, 24 rolls per pallet

**Features:**

- a) Integrated moisture vapor barrier
- b) Hides minor subfloor defects
- c) Improves walking comfort under foot
- d) Non-absorbent, resists mold & mildew
- e) Thermal comfort, floors feel warmer

**Warranty:** 10 Year residential warranty

Greatmats.com  
117 Industrial Ave  
Milltown, WI 54858  
V: 877-822-6622  
F: 866-895-5550  
info@greatmats.com  
revised 3/2015