

30µ UV-cured matte urethane (Topseal)

clear wear layer

printed layer

backing layer

high-density cloth

color layer

Product Specifications Wood Grain DAKOTA Vinyl Flooring Roll

SKU LWood-Dakota

Wood Grain Dakota is a slightly textured sheet that evokes the open grain of oak and the nuance of knot-free, quarter-sawn plank. It is ideal for corporate, healthcare, retail and hospitality applications.

Topseal is a factory-applied urethane finish that protects the floor, reduces scuffing and simplifies routine maintenance. Topseal is applied in a 30-micron wear layer and extends the life of the flooring by protecting it from

wear due to staining, soiling and scuffing.

STANDARD SIZES (nominal) Overall

thickness: 0.080" (2.0 mm)

Wear layer thickness: 0.020" (0.5 mm) Roll size: 6' (1.8 m) wide x 60' (18.3 m) Weight: 0.6 lbs./sq. ft., 230 lbs./roll

Colors: Fourteen available

GREEN FEATURES

- Formulated for microbial resistance
- Formulated for low VOCs
- 20 40% post-industrial recycled content
- Contributes towards LEED MR 4.1 and MR 4.2
- Indoor Air Quality Certified
 - Conforms to CA Specification 01350
- LEED Low Emitting Materials
 - Adhesives and Sealants: LEED IEQ Credit 4.1
- Flooring Systems: LEED IEQ Credit 4.3

10-YEAR LIMITED WARRANTY

Pattern Repeat (nominal)

Machine Direction: 35.8" (910 mm) Cross Direction: 17.8" (451 Mm)

TECHNICAL DATA

.Type 1, Grade1, Class B
Pass
95
Neolite: 1.00
0.31%, 1,000 cycles
1,300 psi
0.003" residual
25,000 cycles - Wear: 4.5, Color: 4.5, Index: 4.6
0.58% loss
Pass
Pass
Class 1 ≥0.45 watts/cm ²
No Change

Greatmats.com 117 Industrial Ave Milltown, WI 54858 P: 877-822-6622 F: 715-825-4928 info@greatmats.com