



# E-Grip III Adhesive Specs

PHYSICAL DATA			
Adhesive Type:	Single component polyurethane		
Color:	Gray	Maximum RH:	85% per ASTM
Antimicrobial:	Yes		F-2170
Adhesive Cure System:	Moisture-cured	Freeze/Thaw Stability:	Stable
VOC Content:	0 lbs/gal (calculated)	Application Temp:	40°F to 100°F
Solvents:	0 lbs/gal (calculated)	Flashpoint:	> 500°F
Moisture Vapor:	Maximum 5.5 lbs per	Shelf Life:	12 Months
Emission of Concrete Floor:	ASTMF 1869	Working Time:	30-40 mins

TROWEL SIZE	APPROX. COVERAGE
1/16" x 1/32" x 5/64" U-notch*	120 sq ft/gal
1/16" x 1/16" x 1/16" square notch	95 sq ft/gal
1/8" x 1/8" x 1/8" square notch	60 sq ft/gal

\*Recommended trowel size for 3.2mm material

TECHNICAL DATA
For technical data, please call 1.800.322.1923

HEALTH & HAZARD RATINGS		
	NFPA	HMIS
Health	1	1
Fire	0	0
Reactivity	0	0
Protective Equipment	None	C

For handling and precautionary information, reference the product label and material safety data sheet.

Greatmats.com  
 117 Industrial Ave  
 Milltown, WI 54858  
 V: 877-822-6622  
 F: 866-895-5550  
 info@greatmats.com  
 revised 6/2014