



## Product Specifications

### Product: Outdoor Play and Patio Tile

**MODULE SIZE:** 1 tile = 4 square feet

Width 24"

Length 24"

Thickness 1"

**MODULE WEIGHT:** 16 lbs per tile  
Per Square Foot: 4 lbs

**MATERIAL:** Recycled Rubber Tires with Urethane Binding Agent  
Density of Shore A 55-65 degrees

<b>FLAME SPREAD:</b>	ASTM E108	Class A
<b>FLAMMABILITY:</b>	ASTM E648	Class II
<b>FLAMMABILITY:</b>	ASTM 2859	Pass
<b>TOXICITY:</b>	ASTM 2075	Lead free
<b>SLIP RESISTANCE:</b>	ASTM F1677	Dry .063, Wet .052
<b>SKID RESISTANCE:</b>	ASTM E303	Dry 96. Wet 47
<b>TENSILE STRENGTH:</b>	ASTM D412	1175.3 psi
<b>WEAR RESISTANCE:</b>	ASTM D3884	1.64% Loss/3000c
<b>UV RESISTANCE:</b>	QPanel QUV	<3.0/4032 ksqm
<b>HEAD IMPACT ATTENUATION:</b>		2 feet

**SUPPORT STRUCTURE:** Peg legs understructure, raised tile for drainage

**WEIGHT LOADING:** Designed for human traffic and furnishings

**SURFACE TEXTURE:** Slight granular surface texture

**MODULAR DESIGN:** Square with Flat Sides.  
Can be installed with connector pins that fit into the tile sides, and connect the tiles laterally.

**GROUND SURFACES:** Designed for Installation on any Hard Flat Surface

**SHIPPING:** Palletized and shrink wrapped on 4x4 ft. pallets

**WARRANTY:** 5 Year Warranty

Greatmats.com  
117 Industrial Ave  
Milltown, WI 54858  
V: 877-822-6622 F: 866-895-5550  
info@greatmats.com  
revised 6/2014