



Product Specifications

Product: Roof and DeckTop Tile

MODULE SIZE: 1 tile = 4 square feet

Width 24"

Length 24"

Thickness 1-3/8"

MODULE WEIGHT: 21 lbs per tile

Per Square Foot: 5.25 lbs

MATERIAL: Recycled Rubber Tires with Urethane Binding Agent
Density of Shore A 55-65 degrees

| | | |
|--------------------------|------------|------------------|
| FLAME SPREAD: | ASTM E108 | Class A |
| FLAMMABILITY: | ASTM E648 | Class II |
| FLAMMABILITY: | ASTM 2859 | Pass |
| TOXICITY: | ASTM 2075 | Lead free |
| SLIP RESISTANCE: | ASTM D2047 | .84 |
| SKID RESISTANCE: | ASTM E303 | Dry 96. Wet 47 |
| TENSILE STRENGTH: | ASTM D412 | 1175.3 psi |
| WEAR RESISTANCE: | ASTM D3884 | 1.64% Loss/3000c |
| UV RESISTANCE: | QPanel QUV | <3.0/4032 ksqm |

SUPPORT STRUCTURE: Peg legs understructure, raised tile for drainage

WEIGHT LOADING: Designed for human traffic and furnishings

SURFACE TEXTURE: Slight granular surface texture

MODULAR DESIGN: Square with Flat Sides.

GROUND SURFACES: Designed for Installation on any Hard Flat Surface

SHIPPING: Palletized and shrink wrapped on 4x4 ft. pallets

WARRANTY: 5 Year Warranty

Greatmats.com
117 Industrial Ave
Milltown, WI 54858
V: 877-822-6622 F: 866-895-5550
info@greatmats.com
revised 6/2014