



## Installation and Maintenance

### Eco Interlocking Carpet Tiles

>>>Please note<<<

*Eco Interlocking Carpet Tiles have a ribbed design. When installing your Eco Interlocking Carpet Tiles, place each tile with the nap or "pile" facing the same direction.*

Typical installation of these tiles is as follows:

First, clean your sub floor removing all dirt, grease or debris.

Start in one corner of the room with a carpet tile and add tiles outward along the adjacent walls, removing extra border strips. Continue to add tiles making sure to keep the nap of the carpet facing the same direction for each tile.

When approaching an opposite wall, make sure you cut the tiles to fit the area, leaving a gap of 1/2". This gap will accommodate expansion and contraction of the floor tiles in varied temperature ranges.

Note: When piecing interlocking carpet tiles together, adhesives are usually not used since the weight of the locked together product is usually enough to keep the floor tiles from moving. However, if you do experience movement and would like to ensure that the tiles do not move; double-sided tape or mat tape can be used around the perimeter of the installation to prevent any movement.

For maintenance:

The recommended cleaning instructions typically include vacuuming the tiles on a medium setting to remove any loose or dry crumbs, dust, or debris.

To clean harder set-in stains or liquids, the carpet tiles may be wiped with a damp rag or can be temporarily removed and cleaned with warm running water in a sink or tub.

Greatmats.com  
117 Industrial Ave  
Milltown, WI 54858  
V: 877-822-6622  
F: 866-895-5550  
info@greatmats.com  
revised 9/2014