



## Product Specifications for Gym Floor Cover 22 oz Vinyl

<b>WARRANTY:</b>	10 Years pro-rata
<b>OVERALL WEIGHT:</b>	22 oz./sq./yd. +/- 5%
<b>SUBSTRATE:</b>	5 oz. woven polyester
<b>COATING:</b>	17 oz. PVC with approximately 50% on each side
<b>TENSILE STRENGTH:</b>	295 lbs. x 285 lbs. (ASTM D5034)
<b>TEAR STRENGTH:</b>	110 lbs. X 75 lbs. (ASTM D2261)
<b>FLAME RESISTANCE:</b>	<b>Must meet these specifications:</b> NFPA-701 Large scale, Boston Fire Marshall, Calif. Fire Marshall, UL-214, U.S. Military spec. MIL-C-20696. Testing per FED STD 191 Method #5903 for self-extinguishing characteristics.

### **Mildew and Odor**

<b>RESISTANCE:</b>	Must contain fungicide and odor inhibitor equal to "Troysan" to contain bacterial growth and odor.
<b>CONSTRUCTION:</b>	Fabric selections to be 10 ft. wide sections or as required. Heat sealed sections to be welded with a minimum 1" wide seam that is as strong as the fabric itself.

*Please note that the values above represent typical data and are subject to slight variation.*

Greatmats.com  
117 Industrial Ave  
Milltown, WI 54858  
877-822-6622  
info@greatmats.com