

Classic Interlocking Stall Mats Product Specifications

DESCRIPTION:

Classic Interlocking Stall Mats are vulcanized using recycled rubber from tires. They are designed to withstand the pressure of horses and/or heavy loads. These mats are 4 feet x 6 feet and are 3/4 inch thick and feature a smooth surface on both sides.

BENEFITS: Excellent traction, Non-absorbent, Durable, Will not lift or curl, Easy to clean, Flat bottom, Insulates.

WEARING SURFACE: 100% recycled vulcanized rubber throughout.

TOLERANCE: Thickness tolerance ± 3/32 inch.

COLOR: Black with miniscule white specks throughout.

OPTIONS: Interlocking format for non-adhesive installation.

MATERIAL PROPERTIES:

Shore Hardness:	ASTM 2240	65
Compression Set:	ASTM D395	8.49%
Taber Abrasion:	ASTM C501	0.1725 mg/cycle @ 1000 cycles 0.1442 mg/cycle @ 2000 cycles
Tensile Strength:	ASTM D412	321 psi.
Elongation at Break:	ASTM D412	180%.
Tear Resistance:	ASTM D624	122.5 lbs/in.
Moisture Absorption:	ASTM D570	0.13%.
Coefficient of Friction	ASTM C1028	Dry=1.25, Wet=1.01
Critical Radiant Flux	ASTM E648-03	0.08 Watts/cm2

WARRANTY: Greatmats offers a Manufacturer's 15 year Limited Equine Warranty on the Classic Stall Mats.

Greatmats.com 877-822-6622 info@greatmats.com page 1

Greatmats Classic Interlocking Stall Mats Product specifications - continued

- Vulcanized rubber mats insulate, cushion, and give excellent traction, even when wet.
- Takes the blows—a three quarter inch of solid vulcanized rubber between your investment and potential damage.
- Recommended uses are for truck boxes, dog kennels, workshops, anti-fatigue applications, mud rooms, tack rooms, and more.
- Mats can be die cut for vibration pads, seals, wear pads, under equipment, or on rooftops.

INSTALLATION:

- Have surface as level as possible to ensure that the mats will lie flat.
- Measure the area where the mat will lie. Mark the desired mat with chalk and cut to fit using a utility knife and straight edge as a cutting guide.

MAINTENANCE: • Clean sweep or hose down.

Greatmats.com 117 Industrial Ave Milltown, WI 54858 Toll free: 877-822-6622 Direct voice: 715-653-6100

info@greatmats.com Revised: 11/2023

Greatmats.com 877-822-6622 info@greatmats.com page 2