

Pacific Rolled Rubber Flooring Product Specifications

Material:	Recycled crumb rubber.
Weight:	3/8 inch – approx. 2.1 lbs. sq/ft. 1/2 inch – approx. 2.5 lbs. sq/ft.
Colors:	Black or 20% standard single color fleck.
Design:	Continuous rolls of rubber flooring.
Sizes:	48 inch X 50 ft standard roll sizes.
Packed:	Shrink wrapped on pallets.
Flammability:	Meets federal regulation #DOC FF1-70.
Installation:	Full spread glue down.
Maintenance:	Damp mop and let dry.
Leadtime:	Generally less than 7 days.

Specific Technical Data

Density:	ASTM D3676	68.3 lbs/cubic foot
Hardness:	ASTM D2240	Shore A65 +/- 5
Slip Resistance:	ASTM D C1028	Friction Coefficient .084-.090
Abrasion:	ASTM D4060	2,000 cycles taber abraser 1kg, .329-.35g loss
Flammability:	ATSM E648	Critical Radiant Flux <0.10 W/cm ²
Acoustics:	Excellent	
Chemicals:	Resistant to most acids and chlorine	
VOC's:	No measurable units	

Greatmats.com
117 Industrial Ave
Milltown, WI 54858
V: 877-822-6622
F: 715-825-4928
info@greatmats.com