


PRODUCT DATA SHEET: Flexigrid

SIZES & WEIGHTS

<i>All dimensions are nominal</i>	Height (in)	Lengths (ft)	Widths (ft)		Weight (lbs/sq.ft)
<i>Tolerances</i>	<i>+/- 0.05"</i>	<i>0+1.0'</i>	<i>+/- 1/2"</i>		
Flexigrid	3/4"	16' & 33'	2'	3'	2.0



General

APPEARANCES	Open grid design with textured surface.
COLORS	Black homogeneous stable color.
DURABILITY	One Piece welded construction for maintenance free life.
WORKABILITY	Flexible construction is easy to cut and shape on site. Supplied in rolls with top ribs facing outwards. Requires inverting once rolled out prior to use.
USES	Heavy duty for indoor or outdoor locations.

TECHNICAL DATA

ACOUSTIC	Excellent sound absorption properties.
CHEMICAL	Resistant to most acids, alkalines and acids (for specific chemical resistances, see http://www.plastexmatting.com/uploads/4/4/0/0/44003899/pvc-chemical-resistance.pdf)
COMPOSITION	Flexible Polyvinyl Chloride (PVC)
ENVIRONMENT	It has been determined under the guidelines for the State of California Safe Drinking Water and Toxic Enforcement Act of 1986 (Prop 65), that no warning labels or warning provisions are required for Flexigrid. Made from post-industrial recycled PVC, always with a minimum content of 30% up to 100%. Plastex does not use any substance currently

included in the SVHC (Substances of Very High Concern) list under R.E.A.C.H* in any matting products. All PVC grid products are 100% recyclable.

*Registration, Evaluation, Authorization, and Restriction of Chemical substances

FIRE	DIN 4102 Part 1 – Classification B2
HYGIENE	Non-porous 100% Virgin PVC – Inhibits the growth of bacteria.
REVERSION	Thermoplastic shrinkage can result in size reductions up to 2%. Accelerated in hot environments.
SLIP RESISTANCE	ASTM F 1677 – Dry/Wet 0.6/0.52 DIN51130: R11, V10
THERMAL	Functional -9° F + 140° F(Slight variation may occur at temperature extremes).
UV LIGHT	Resistant to PVC degradation; uncolored PVC material – BS EN 607 = Delta E 1.02.
WARRANTY	4 Years. http://www.plastexmatting.com/uploads/4/4/0/0/44003899/warranty.pdf

ANCILLARIES



5/8" x 2 3/16" x 6'6"
(22mm x 50mm x 2m)

2 3/16" Aluminum edging strip

Supplied in sections of 6'6" (2m) length
with fixing screws and plugs.

Color: Anodized Aluminum.

Greatmats Specialty Flooring

**117 Industrial Ave
Milltown, WI 54858**

877-822-6622

F: 715-825-4928

info@greatmats.com

www.greatmats.com