

## Technical Specifications SoftCarpet Tiles

SKU EFICT

A carefully selected blend of coarse polypropylene and coarse polyester fiber is produced with needlepunch and is specially needled through the material over two million needle punches per square meter to produce a pile. The product is back-coated with a synthetic resin.

### Technical Data

Blend of fibres		Polypropylene & Polyester
Dimension	Length	30M
	Width	2.0M
Thickness		6.5m/m
Weight	Fibre	1050 g/m <sup>2</sup>
	Resin	200 g / m <sup>2</sup>
Total weight		1250 g / m <sup>2</sup>

### Performance

Combustibility		Difficult to set ablaze, flame retarding According to FMVSS No.302
Soil resistance		3M Scotchgard resistance
Static electricity		Anti-static treatment < 2.5KV
Abrasion strength		Minimum rating 4. According to NES M0076
Sound insulation		22dB, Test in accordance with DIN 4109. 23dB, Test in accordance with Empa norms.
Color fastness	Light	Minimum rating 4.
	Shampoo	Minimum rating 6.

### Recommended uses:

Heavy-duty use, offices, kitchens, hotels, museums, clubs, lounges, libraries, exhibitions, restaurants, bars, showrooms, university lecture rooms and corridors etc.

Greatmats.com  
117 Industrial Ave  
Milltown, WI 54858

V: 877-822-6622  
F: 866-895-5550  
info@greatmats.com