



MATLAY SPECIFICATIONS

Matlay marley-type dance flooring is manufactured of specially-formulated poly vinyl chloride (PVC vinyl) with a non-skid matte finish. It is great for multi-purpose use, all forms of dance and most stage areas. Matlay is reversible with black on one side and your choice of gray or white on the other

OUTDOOR USE AND PRECAUTIONS

On an outdoor surface, because of the “sun heat”, only the white side up of the white/black floor may be used. The gray and black floor gets too hot in the sun and can cause burns. Keep in mind possible inclement weather, as this could cause safety concerns as well. **Sweat, any kind of humidity or moisture can cause a slippery surface. If it gets wet, it must be dried off before anyone gets on the floor.**

SPECIFICATIONS

Weight: Approx 2 lbs per linear foot
Thickness: 0.044” (1.1mm)
Full Roll Dimensions: 6' x 60', lengths will be longer than stated
Color: Reversible Gray/Black or White/Black
Additional lengths available

TEMPERATURE

Like all “Marley” or PVC vinyl sheeting, Matlay can be affected by temperature, humidity, applied pressure, etc. It will expand or contract to some degree. In extreme temperatures such as approx -20°F, the Matlay could “cold crack” with impact such as dropping the roll. At approx 160°F, it can cause minor shrinkage. If the rolls of Matlay have been exposed to extreme temperature, then bring them back to room temperature before unrolling them.

INSTALLATION

Installation is semi-permanent with top tape-down application. See Matlay Stretching & Tape-Down Instructions.

CLEANING & MAINTENANCE

See Matlay Cleaning Instructions.

STORAGE

Ensure Matlay is dry, clean of any foreign substances (such as grease, oil, dirt, etc) and all tape is removed before rolling it up for storage. Matlay should be rolled evenly and tightly, and then stored horizontally on an even, flat and smooth surface with no heavy objects on top of it.

Greatmats.com

117 Industrial Ave - Milltown, WI 54858

info@greatmats.com