

LVT Total Comfort



IMPACT / STEP SOUND REDUCTION & COMFORT UNDERLAYMENT FOR FLOATING VINYL PLANK & OTHER FLOATING FLOORING PRODUCTS

Approved For Use With:
 Floating Luxury Vinyl Plank
 Floating Laminate Floors
 Floating Engineered Hardwood

Integrated Vapor Barrier for Basement & Slab on Grade Applications
 Impact Sound Control for 2nd Floor & Multi-Family Applications
 Reduces In Room Step Sound - Highly Resistant to Indentation
 Zero Formaldehyde - Hypo Allergenic - No Pthalates or VOC's

PRODUCT DESCRIPTION
 High Performance Recycled Foam & Agglomerated Cork Underlayment Plus Vapor Retarding Barrier for Floating Flooring Applications

ENVIRONMENTAL PROPERTIES
 Recyled Content (LEED - MR 4)
 Rapidly Renewing Content (LEED -MR 7)
 (85%+ Recycled & Renewable Content)

PHYSICAL AND MECHANICAL PROPERTIES
 Density: 11.5 to 13 lbs. ft³
 Tensile Strength: > 150 KPa
 Compression (100PSI): <30%
 Recovery: > 90%
 Perm Rating: = / < 0.5
 Durability: Lifetime of the Building



ACOUSTICAL RESULTS
 (ASTM E 492 -09 / E989 - NGC Testing Services)
 IIC 68 -6" Concrete Slab - Drywall Ceiling
 (ASTM E2179) Delta IIC Rating -20
 (ASTM E 90-09 / E413 - NGC Testing Services)
 STC 60 -6" Concrete Slab- Drywall Ceiling

PACKAGING*
 1m x 9.28m x.8mm (100 s/f)
 (39.4" x 30.47' x 0.071")
 * Others sizes available upon request
 35 Rolls per Pallet

OTHER FEATURES & BENEFITS
 Helps Bridge Minor Subfloor Defects
 Thermal Insulator - Floors Feel Warmer
 Reduces "Hollow" Sound in Floors
 Rated for Multi-Family Applications
 Resistant to Mold & Mildew