

## BestGym Rubber Tile Interlocking Product Specifications

### Technical Data

Nominal Dimensions - Interlocking: \_\_\_\_\_ 25 3/4" x 25 3/4" x 3/8" (9mm) Smooth

Finish: \_\_\_\_\_ Smooth

Area Per Tile: \_\_\_\_\_ 4.6 sq. ft.

Weight Per Tile: \_\_\_\_\_ 10 lbs.

Quantity Per Pallet: \_\_\_\_\_ 100 tiles

ASTM D2047 – Coefficient of Friction: \_\_\_\_\_ >0.7

ASTM E648 (NFPA 253) –

Critical Radiant Flux: \_\_\_\_\_ Class II, >0.22 W/cm<sup>2</sup>

ASTM D2240 - Hardness: \_\_\_\_\_ Shore A; 60 +/- 5

ASTM F970 - Static Load Limit: \_\_\_\_\_ Pass

ASTM F970 (Modified) - Max Weight: \_\_\_\_\_ 500 PSI

ASTM E90 Sound Transmission Loss: \_\_\_\_\_ 52 STC\*

ASTM E492 Impact Sound Transmission: \_\_\_\_\_ 52 IIC\*

ASTM E2179 Delta Impact Insulation: \_\_\_\_\_ 22 ΔIIC\*

Acclimation Time: \_\_\_\_\_ 48 Hours

Storage & Acclimation Temperature: \_\_\_\_\_ 65° - 85° F

*\* 6" Concrete, No Drop Ceiling*

### Features

- Non-Porous Material
- PVC Free
- Made From Recycled Materials
- Qualifies for LEED Credits
- Extremely Durable
- Shock-Absorbing
- Noise-Reducing Material
- Easy To Maintain
- Excellent Slip Resistance
- Excellent Chemical Resistance

### Additional Information

Approved Adhesives:

BestGym Excelsior MS-700 Modified Silane Adhesive  
BestGym Excelsior EW-710 Epoxy Wet-Set Adhesive

Approved Floor Finisher:

BestGym Excelsior PF-960 Performance Gloss Finish

BestGym requires that a finish be installed following installation.

Greatmats.com  
117 Industrial Ave  
Milltown, WI 54858  
Toll free: 877-822-6622  
Fax: 715-825-4928  
info@greatmats.com  
6/2017