

### BestGym Tile PR-930 Floor Finish Remover

**SKU: GEXPFR**

#### PRODUCT DESCRIPTION

PR-930 is a finish remover specifically designed to remove topically applied flooring finishes over resilient flooring products that are sensitive to alkalinity, such as rubber flooring and crumb/recycled rubber flooring. PR-930 allows for the removal of these finishes without causing damage to pH sensitive flooring products. PR-930 is designed to remove multiple layers of floor finish, even if heavily soiled or thickly applied.

#### FEATURES

- **Low Alkalinity**
- **Reduces Application & Removal Times**
- **Compatible with pH Sensitive Flooring**
- **Prevents Discoloration of Sensitive Flooring**
- **Compatible with Most Resilient Flooring Products**
- **Normal Stripping or Heavy Removal**

#### TECHNICAL INFORMATION

Unit Size:	<b>1 Gallon</b>
Weight:	<b>8.07 lbs.</b>
VOC:	<b>9%</b>
pH:	<b>8-9</b>
Flash Point:	<b>176° F</b>
Normal Stripping Dilution:	<b>32 oz. per Gallon</b>
Heavy-Duty Removal Dilution:	<b>64 oz. per Gallon</b>
Diluted Gallons Per Unit:	<b>2 – 4 Gallons</b>
Coverage Per Diluted Gallon:	<b>75 – 100 sq. ft.</b>
Coverage Per Unit:	<b>150 - 400 sq. ft.</b>
Shelf Life:	<b>1 Year</b>
Storage Temperature:	<b>50° - 75° F</b>

## **BestGym Tile PR-930 Floor Finish Remover – Continued**

### **COLOR STABILITY**

Prior to use, ensure that the flooring material is color-stable, as manufacturer is not responsible for color changes within flooring products.

### **APPLICATION INSTRUCTIONS**

Prior to cleaning, sweep, dust mop and/or vacuum to remove dirt, dust and debris from flooring surface. Do not use vacuums that contain beater bars or electric brooms with hard plastic bottoms and/or no padding, as these devices may cause discoloration, scratching and loss of sheen.

Mix PR-930 with clean, potable water in a clean mixing container. Adjust dilution rate based on amount of removal required. Apply cleaner directly to floor with a clean mop, pad or sponge and let stand for 10-20 minutes. Scrub area using a rotary floor machine or auto-scrubbing machine to remove finish. Be sure to use a cleaning pad approved for use with the floor covering, as aggressive pads could damage, mar or diminish the sheen of some flooring products. Maintain a wet surface while scrubbing to avoid damaging flooring product and apply more material as necessary.

Remove cleaning solution with an auto-scrubber or a wet vacuum. Dispose of stripping solution in accordance with local, state and federal disposal regulations. Once removed, rinse flooring surface with clean, cold potable water and a clean mop, pad or sponge.

**FOR PROFESSIONAL USE ONLY. PLEASE CONSULT ALL ASSOCIATED TECHNICAL DATA SHEETS, SAFETY DATA SHEETS AND WARRANTY INFORMATION PRIOR TO INSTALLATION.**

Greatmats.com  
117 Industrial Ave  
Milltown, WI 54858  
Toll free: 877-822-6622  
Fax: 715-825-4928  
info@greatmats.com  
6/2017