



LVT Solid 20 Mil Carton of 15

Product Specifications

SKU: Solid LVT20

Tile Size: 18.5 x 18.5 x 1/8 inch
Weight: 40 lbs.
Color: Black, White
Texture: Smooth top design surface
Material: Vinyl
Surfaces Install: Glue down on hard surface
Shipping: 15 pieces per 20x3x20 per carton, 44 cartons per standard 4x4 ft pallet

Features:

PRODUCT STANDARDS		
ITEM	STANDARD	RATING
HUD/FHA		Passes
Flexibility	ASTM F137	1 inch Mandrel – No crack/break
Dimensional Stability	ASTM F2199	Max 0.020 in/lin. ft.
Squareness	ASTM F540	0.010 inch Max
Static Load	ASTM F970 Mod.	2,000 PSI; Resid. Indent \leq 0.005 inch
Residual Indentation	ASTM F1917	< 8% Avg/ 10 Single Value
Flooring Radiant Panel	ASTM E648	Class 1; \geq 0.45 watts/cm ²
Smoke Density	ASTM E662	\leq 450
Slip Resistance	ASTM C1028	\geq 0.5 Leather; 0.6 Rubber
Resistance to Light	ASTM F1515	Passes
Acoustic IIC	ASTM E492	60 – 6 inch concrete with drop ceiling
Acoustic STC	ASTM E90	62 – 6 inch concrete with drop ceiling
Chemical Resistance	ASTM F925	Passes
Resistance to Heat	ASTM F1514	Passes

Greatmats.com
117 Industrial Ave
Milltown, WI 54858
Toll free: 877-822-6622
Fax: 715-825-4928
info@greatmats.com