



Enterprise Commercial Carpet Tile Product Specifications

SKU: ETTILE-AN3

General Information

The Enterprise Tile is an extremely durable, hard wearing tile that has specially blended fibers that provide superior scraping and is ideal for wall-to-wall application as well as use in entrances.

This product must be used for interior applications only and be installed by professional installers that have sufficient professional liability insurance coverage (aka Errors and Omissions Insurance) for the project. Caution should be used in the moving and lifting of material; always allow for appropriate equipment and manpower to safely move materials.

Work safe and always follow the relevant safety procedures.

The manufacturer recommends installing and maintaining entrance matting at all outdoor entrances; this will improve air quality, reduce maintenance costs, and lengthen the life of your floors.

Proper glides must be used on all furniture or objects that may slide directly across the entrance flooring, consult the furniture manufacturer for recommendations for use on resilient flooring.

Heavy objects must not be moved directly across the floor; use protective boards.

Direct sunlight can cause UV damage (fading or bleaching) to most interior finishes, so Low E glass should be selected that will reduce the UV transmission to less than 1%. If not, applying 3M™ protection film (or similar) on the windows is recommended.

Do not install any material that has visible defects or damage. A contractor that installs any material that has visible defects or damage assumes responsibility for the damaged material.

All Safety Data Sheets (SDS) and Installation, Maintenance and Warranty requirements must be read, understood and followed.

These instructions supersede any verbal or written instructions from the manufacturer, and must be followed in order for the limited warranty to be in effect.

Enterprise Commercial Carpet Tile Product Specifications – continued

Technical Data	
Tile size	19-11/16 inch x 19-11/16 inch (50 cm x 50 cm) ~ 2.7 square feet per tile
Pile Height	~ 1/4 " (5.2 mm)
Overall Height	~ 7/16 " (11.5 mm)
Yarn	100% Polypropylene Fiber
Pile Weight	47 oz. per sq yard (1600 gr/sq meter)
Total Weight	137 oz per sq yard (4650 gr/sq meter)
Carton size	16 tiles per carton, ~43.2 square feet per case.
Backing	Bitumen
Limited warranty	3 years

Performance	Test Method	Result
Flammability	ASTM D2859	Passes

Adhesive	Moisture Limits	Application Method
MI 1000	≤ 90% RH used wet-set over porous substrates only ≤ 90% RH used semi-dry over non-porous substrates ≤ 95% RH used semi-dry over a porous concrete subfloor	1/32" x 1/16" x 1/32" U-notch trowel (FFA)

Greatmats.com
 117 Industrial Ave
 Milltown, WI 54858
 Toll free: 877-822-6622
 Direct voice: 715-653-6100
 Fax: 715-825-4928
 info@greatmats.com
 3/2025