

PAVESAFE™



GUIDE SPECIFICATIONS

Manufactured in the USA by:



www.pavesafe.com

Updated on 11/17/11.
Supersedes any
previous version. Check
Website for updates.

October 8, 2010-This MS Word document is provided solely as a convenience for spec writers in the drafting process. ECORE International will not be held responsible for the use or alteration of any information contained herein. For a final approved PDF version of these specifications please visit the literature page at www.pavesafe.com.

DIVISION 9 - SECTION 09 65 00
Pavesafe Recycled Rubber Equine Surfacing

PART 1.0- GENERAL

1.1 SUMMARY

- A. The work of this section includes:
 - 1. Recycled rubber equine floor interlocking paver
 - 2. Adhesives
- B. Related Sections: Section(s) related to this section include:
 - 1. Concrete Substrate: Division 3 Concrete Section(s)
 - 2. Plywood Substrate: Division 6

1.2 REFERENCES

- A. Standards listed by reference, including revisions by issuing authority, form a part of this specification section to extent indicated. Standards listed are identified by issuing authority, authority abbreviation, designation number, title or other designation established by issuing authority. Standards subsequently referenced herein are referred to by issuing authority abbreviation and standard designation.
- B. American Society for Testing and Materials (ASTM):
 - 1. ASTM D412 Standard Test Methods for Vulcanized Rubber and Thermoplastic Rubbers and Thermoplastic Elastomers – Tension
 - 2. ASTM D624 Standard Test Method for Tear Strength of Conventional Vulcanized Rubber and Thermoplastic Elastomers
 - 3. ASTM D3389 Standard Test Method for Coated Fabrics Abrasion Resistance (Rotary Platform Abrader)
 - 4. ASTM F1869 Standard Test Method for Measuring Moisture Vapor Emission Rate of Concrete Subfloor Using Anhydrous Calcium Chloride
 - 5. ASTM F2170 Standard Test Method for Determining Relative Humidity in Concrete Floor Slabs Using in situ Probes
- C. South Coast Air Quality Management District (SCAQMD) Rule #1168
 - 1. VOC standards for adhesive and sealant applications
- D. Leadership in Energy and Environmental Design – LEED™
 - 1. International Organization for Standardization™ document, ISO 14021 - Provides guidance on the terminology, symbols, testing and verification methodologies that an organization should use for self-declaration of the environmental aspects of its products and services.

1.3 SYSTEM DESCRIPTION

- A. Performance Requirements: Provide recycled rubber equine flooring, which has been manufactured and installed to maintain performance criteria stated by manufacturer without defects, damage or failure.

1.4 SUBMITTALS

- A. General: Submit listed submittals in accordance with Conditions of the Contract and Division 1 Submittal Procedures Section.
- B. LEED: Provide documentation of how the requirements for credit will be met.
 - 1. List of proposed materials with recycled content. Indicate pre-consumer and post-consumer content.
 - 2. Product data and certification letter indicating percentage of recycled content for both pre-consumer and post-consumer content.
 - 3. Recycled content is defined in accordance with the International Organization for Standardization document, ISO 14021 Environmental labels and declarations.
 - a. Post-consumer material - waste materials diverted from the waste stream after consumer or commercial use.
 - b. Pre-consumer material - materials diverted from the waste stream during the manufacturing process. Excluded are regrind, rework, and scrap.
- C. Product Data: Submit product data, including manufacturer's guide specifications product sheet, for specified products.
- D. Shop Drawings: Submit shop drawings showing layout, profiles and product components, including anchorage, accessories, finish colors, patterns and textures.
- E. Samples: Submit selection and verification samples for finishes, colors and textures.
- F. Quality Assurance Submittals: Submit the following:
 - 1. Certificates: If required, certification of performance characteristics specified in this document shall be provided by the manufacturer.
 - 2. Manufacturer's Instructions: Manufacturer's installation instructions.

Specifier Note: Coordinate paragraph below with Part 3.5 Field Quality Requirements Article herein. Retain or delete as applicable.

- 3. Manufacturer's Field Reports: Manufacturer's field reports specified herein.
- G. Closeout Submittals: Submit the following:
 - 1. Operation and Maintenance Data: Operation and maintenance data for installed products in accordance with Division 1 Closeout Submittals (Maintenance Data and Operational Data) Section. Include methods for maintaining installed products and precautions against cleaning materials and methods detrimental to finishes and performance.
 - 2. Warranty: Warranty documents specified herein.

1.5 QUALITY ASSURANCE

- A. Qualifications:
 - 1. Installer Qualifications: Installer experienced in performing work of this section who has specialized in installation of work similar to that required for this project.
 - a. Certificate: When requested, submit certificate indicating qualification.
 - 2. Manufacturer's Qualifications: Manufacturer capable of providing field service representation during construction and approving application method.

Specifier Note: Paragraph below should list obligations for compliance with specific code requirements particular to this section. General statements to comply with a particular code are typically addressed in Conditions of Contract and Division 1 Regulatory Requirements Section. Regulatory Requirements: [specify applicable requirements of regulatory agencies].

- B. Mock-Ups: Install at project site a job mock-up using acceptable products and manufacturer-approved installation methods. Obtain Owner and Architect's acceptance of finish color, texture and pattern, and workmanship standard. Comply with Division 1 Quality Control (Mock-Up Requirements) Section.
 - 1. Mock-Up Size: [specify mock-up size].

2. Maintenance: Maintain mock-up during construction for workmanship comparison; remove and legally dispose of mock-up when no longer required.
 3. Incorporation: Mock-up may be incorporated into final construction upon Owner's approval.
- C. Pre-installation Meetings: Conduct pre-installation meeting to verify project requirements, substrate conditions, manufacturer's instructions and manufacturer's warranty requirements. Comply with Division 1 Project Management and Coordination (Project Meetings) Section.
- D. Pre-installation Testing: Conduct pre-installation testing as follows: [specify substrate testing; consult with flooring manufacturer].

1.6 DELIVERY, STORAGE & HANDLING

- A. General: Comply with Division 1 Product Requirements Sections.
- B. Ordering: Comply with manufacturer's ordering instructions and lead time requirements to avoid construction delays.
- C. Delivery: Deliver materials in manufacturer's original, unopened, undamaged containers with identification labels intact.
- D. Storage and Protection: Store materials at temperature and humidity conditions recommended by manufacturer and protect from exposure to harmful weather conditions.

1.7 PROJECT CONDITIONS

- A. Temperature Requirements: Maintain air temperature in spaces where products will be installed for time period before, during and after installation as recommended by manufacturer.
- B. Field Measurements: Verify actual measurements/openings by field measurements before fabrication; show recorded measurements on shop drawings. Coordinate field measurements and fabrication schedule with construction progress to avoid construction delays.

1.8 WARRANTY

- A. Project Warranty: Refer to Conditions of the Contract for project warranty provisions.
- B. Manufacturer's Warranty: Submit, for Owner's acceptance, manufacturer's standard warranty document executed by authorized company official. Manufacturer's warranty is in addition to and not a limitation of, other rights Owner may have under Contract Documents.

Specifier Note: Coordinate paragraph below with manufacturer's warranty requirements.

1. Warranty Period: [Specify term] years commencing in Date of Substantial Completion.

1.9 MAINTENANCE

- A. Extra Materials: Deliver to Owner extra materials from same production run as products installed. Package products with protective covering and identify with descriptive labels. Comply with Division 1 Closeout Submittals (Maintenance Materials) Section.
 1. Quantity: Furnish quantity of recycled rubber flooring units equal to [specify %] of amount installed.
 2. Delivery, Storage and Protection: Comply with Owner's requirements for delivery, storage and protection of extra materials.

PART 2.0 - PROPRIETARY MANUFACTURER/PRODUCTS

Specifier Note: Retain article below for proprietary method specification. Add product attributes, performance characteristics, material standards and descriptions as applicable. Use of such phrases as "or equal" or "or approved equal" or similar phrases may cause ambiguity in specifications. Such phrases require verification (procedural, legal and regulatory) and assignment of responsibility for determining "or equal" products.

2.1 MANUFACTURER: ECORE International™

- A. Address: 715 Fountain Ave., Lancaster, PA 17601; Telephone: (800) 322-1923, (717) 295-3400; Fax: (717) 295-3414; Email: info@ecoreintl.com

2.2 PROPRIETARY PRODUCT(S)

- A. Pavesafe™ Recycled Rubber Equine Flooring, Adhesives and Sealants manufactured by ECORE for indoor/outdoor applications
 - 1. Pavesafe™ recycled rubber equine interlocking paver flooring
 - 2. Pavesafe™ recycled rubber equine tile flooring
 - 3. Pavesafe™ recycled rubber wall tile
 - 4. Pavesafe™ recycled rubber border edges
 - 5. Pavesafe™ recycled rubber beveled edges
 - 6. E-Grip III™ single-component, zero-VOC, urethane, adhesive

2.2.1 Pavesafe™ Recycled Rubber Equine Interlocking Paver Flooring

- A. Product Name: The non-laminated, single-ply, rubber surface furnished under this specification shall be ECORE's **Pavesafe** Recycled Rubber Equine Interlocking Paver Flooring.
- B. Material: Made from 100% recycled SBR (Styrene-Butadiene Rubber) tire rubber.
- C. Dimension: ECORE International's Pavesafe™ Recycled Rubber Equine Interlocking Paver Flooring surface will have an overall thickness of _____ (specify: 7/8" [22.2 mm] standard or 1 3/4" [44.4 mm] special order in 7 3/4" x 6 1/4" x 4 3/8" [197mm x 159 mm x 111mm])
- D. Weight: 7/8" – 8.51 lb/ft² [41.5 kg/m²]
1 3/4" – 17.0 lb/ft² [83.0 kg/m²]
- E. Standard Tolerances: ± 1/16"
- F. Colors: Specify color from manufacturer's standard colors.
- G. Tensile Strength: (ASTM D412) 140 lb/in² min.
- H. Tear Strength: (ASTM D624) 50 lb/in min.
- I. Abrasion Resistance: (ASTM D3389) Less than 1g loss after 1,000 cycles

2.2.2 Pavesafe™ Recycled Rubber Equine Tile Flooring

- A. Product Name: The non-laminated, single-ply, rubber surface furnished under this specification shall be ECORE's **Pavesafe** Recycled Rubber Equine Tile Flooring.
- B. Material: Made from 100% recycled SBR (Styrene-Butadiene Rubber) tire rubber.
- C. Dimension: ECORE International's Pavesafe™ Recycled Rubber Equine Tile Flooring surface will have an overall thickness of _____ (specify: 5/8" [15.8 mm] standard or 1 1/4" [31.8 mm] special order or 1 3/4" [44.4mm] special order in 24" x 24" [609.6mm x 609.6 mm])
- D. Weight: 5/8" – 2.5 lb/ft² [12.2 kg/m²]
1 1/4" – 7.0 lb/ft² [34.2 kg/m²]
1 3/4" – 17.0 lb/ft² [83.0 kg/m²]
- E. Standard Tolerances: ± 1/16"
- F. Colors: Specify color from manufacturer's standard colors.
- G. Tensile Strength: 90 lb/in² min.

- (ASTM D412)
- H. Tear Strength: 30 lb/in min.
(ASTM D624)
- I. Abrasion Resistance: Less than 1g loss after 1,000 cycles
(ASTM D3389)

2.2.3 Pavesafe™ Recycled Rubber Wall Tiles

- A. Product Name: The non-laminated, single-ply, rubber surface furnished under this specification shall be ECORE's **Pavesafe** Recycled Rubber Wall Tiles.
- B. Material: Made from 100% recycled SBR (Styrene-Butadiene Rubber) tire rubber.
- C. Dimension: ECORE International's Pavesafe™ Recycled Rubber Wall tile surface will have an overall thickness of _____ (specify: 5/8" [15.8 mm] standard or 1 1/4" [31.8 mm] special order or 1 3/4" [44.4mm] special order in 39 3/8" x 19 5/8" [1,000mm x 500mm])
- D. Weight: 5/8" – 2.5 lb/ft² [12.2 kg/m²]
1 1/4" – 4.9 lb/ft² [23.9 kg/m²]
1 3/4" – 7.1 lb/ft² [34.7.0 kg/m²]
- E. Standard Tolerances: ± 1/16"
- F. Colors: Specify color from manufacturer's standard colors.
- G. Tensile Strength: 60 lb/in² min.
(ASTM D412)
- H. Tear Strength: 10 lb/in min.
(ASTM D624)
- I. Abrasion Resistance: Less than 1g loss after 1,000 cycles
(ASTM D3389)

2.2.4 Pavesafe™ Recycled Rubber Border Edges

- A. Product Name: The non-laminated, single-ply, rubber product furnished under this specification shall be ECORE's **Pavesafe** Recycled Rubber Border Edges.
- B. Material: Made from 100% recycled SBR (Styrene-Butadiene Rubber) tire rubber.
- C. Dimension: ECORE International's Pavesafe™ Recycled Rubber Border Edges will have an overall thickness of 10" [254mm] in 2" x 39" [50.8mm x 990.6mm]
- D. Weight: 22 lb each [9.98 kg]
- E. Standard Tolerances: ± 1/16"
- F. Colors: Specify color from manufacturer's standard colors

2.2.5 Pavesafe™ Recycled Rubber Beveled Edges

- A. Product Name: The non-laminated, single-ply, rubber product furnished under this specification shall be ECORE's **Pavesafe** Recycled Rubber Beveled Edges.
- B. Material: Made from 100% recycled SBR (Styrene-Butadiene Rubber) tire rubber.
- C. Dimension: ECORE International's Pavesafe™ Recycled Rubber Beveled Edge will have a thickness of _____ (specify: 7/8" [22.2 mm] standard or 1-11/16" [42.8 mm])

- | | |
|-------------------------|---|
| D. Weight: | 7/8" - 1.7 lb. each [2.26 kg]
1-11/16" – 14.0 lb. each [6.4kg] |
| E. Standard Tolerances: | ± 1/16" |
| F. Colors: | Specify color from manufacturer's standard colors. |

2.2.6 E-Grip™ III one-component urethane adhesive

- | | |
|--|--|
| A. Product Name: | The one-part urethane adhesive under this specification shall be ECORE's E-Grip™ III one-component urethane adhesive. |
| B. Material: | E-Grip III is a one-component urethane moisture cured, non-sag, permanently elastic adhesive that has excellent adhesion to elastomers, concrete and wood and is engineered for indoor and outdoor applications. |
| C. Adhesive Type: | one-component urethane |
| D. Adhesive Cure System: | moisture cured |
| E. Weight: | 4 gallon pail-56 lbs
2 gallon pail-28 lbs
10.1 oz cartridges |
| F. Color: | medium grey |
| G. VOC Content: | 0 lb/gal calculated |
| H. Freeze/Thaw: | stable |
| I. Application Temperature: | 40° F - 100° F |
| J. Calcium Chloride Test:
(ASTM F1869) | Maximum 5.5 lbs per 1,000 sq. ft. in 24 hrs. |
| K. Relative Humidity (RH) Test
(ASTM F2170) | Maximum 85% |
| L. Flashpoint: | > 500° F |
| M. Shelf Life: | 12 months |
| N. Working Time: | 30-40 minutes |
| O. Trowel: | 1/8" square notched trowel ⁽¹⁾ |
| P. Coverage Rate: | 60 ft ² per gallon (1/8" square notched trowel) |
| Q. SCAQMD Rule #1168 | 0 lb./gal. calculated |

(1) See Pavesafe Installation Manual for instructions.

2.3 PRODUCT SUBSTITUTIONS

- A. Substitutions: No substitutions permitted.

2.4 RELATED MATERIALS

- A. Related Materials: Refer to other sections listed in Related Sections paragraph herein for related materials.

2.5 SOURCE QUALITY

- A. Source Quality: Obtain recycled rubber equine flooring materials from a single manufacturer.

PART 3.0 - EXECUTION

Specifier Note: Revise article below to suit project requirements and specifier's practice.

3.1 MANUFACTURER'S INSTRUCTIONS

- A. Compliance: Comply with manufacturer's product data, including product technical bulletins, product catalog installation instructions and product carton instructions for installation.

3.2 EXAMINATION

- A. Site Verification of Conditions: Verify substrate conditions, which have been previously installed under other sections, are acceptable for product installation in accordance with manufacturer's instructions.

3.3 PREPARATION

- A. Surface Preparation: [specify applicable product preparation requirements].

Specifier Note: Coordinate article below with manufacturer's recommended installation details and requirements.

3.4 ERECTION/INSTALLATION/APPLICATION/CONSTRUCTION

- A. Recycled Rubber Flooring Installation: Comply with Pavesafe Technical Manual for installation procedures and techniques for Pavesafe recycled rubber equine flooring installation.
- B. Finish Color/Textures/Patterns: [specify installation finishes coordinated with finishes specified in Part 2 Products].
- C. Related Products Installation: Refer to other sections listed in Related Sections paragraph herein for related products installation.

3.5 FIELD QUALITY REQUIREMENTS

Specifier Note: Edit paragraph below. Establish number and duration of periodic site visits with Owner and manufacturer, and specify below. Consult with manufacturer for services required. Coordinate paragraph below with Division 1 Quality Assurance Section and Part 1 Quality Assurance Submittals herein. Delete if manufacturer's field service not required.

- A. Manufacturer's Field Services: Upon Owner's request, provide manufacturer's field service consisting of product use recommendations and periodic site visit for inspection of product installation in accordance with manufacturer's instructions.
 - 1. Site Visits: [specify number and duration of periodic site visits].

3.6 CLEANING

- A. Cleaning: Remove temporary coverings and protection of adjacent work areas. Repair or replace damaged installed products. Clean installed products in accordance with manufacturer's instructions prior to Owner's acceptance. Remove construction debris from project site and legally dispose of debris.

3.7 PROTECTION

- A. Protection: Protect installed product and finish surfaces from damage during construction.

Specifier Note: Retain article below to suit project requirements. Article may be used to describe specific criteria requirements of similar products or equipment.

3.8 SCHEDULES

Specifier Note: Retain paragraph below to suit project requirements. Reference a schedule or include a schedule as an attachment, which indicates where to locate products and equipment.

- A. Schedules: [Specify reference to applicable schedules].

END OF SECTION

PAVESAFE™

www.pavesafe.com

Manufactured in the USA by:

ecore™
— INTERNATIONAL —

715 Fountain Ave
Lancaster, PA 17601