



## Performance Beast Rubber Rolls per SF

### Product Specifications

Roll Size: 4' wide by custom length. Minimum length 30 LF.

Roll Thickness: 10.5 mm total: 8mm Vulcanized Composition Rubber base layer plus 2.5 mm Vulcanized Composition Rubber Surface Wear Layer

Roll Weight: 2.4 lbs per sf

Standard Colors: Blue Premium, Dark Gray Premium, Mocha Latte 2, Steel Appeal 2

Premium Colors: Medium Grey Premium, Charcoal Premium, Dark Taupe Premium, Warm Grey Premium

Supreme Colors: Navy Premium, Green Premium, Maroon Premium, Red Premium

Material: High quality post-consumer recycled rubber granules encapsulated in a wear and water-resistant elastomeric network with a fusion bonded reprocessed EPDM surface wear layer.

Performance Criteria	Test Method	Typical Results
Static Load Limit	ASTM F970 @ 250 PSI	0.004" Pass
Slip Resistance / Coefficient of Friction	ASTM D2047	>0.90
VOC's / FloorScore / CHPS / CA 01350	ASTM D5116 Pass	Pass
Color Stability	ASTM F1515	Good
Chemical Resistance	ASTM F925	Good
Abrasion Resistance	ASTM D3389	<1g, 1000 cycle
Resistance to Light by Color Change	ASTM F1515	Pass
Resistance to Heat by Color Change	ASTM F1514	Pass
Flammability – Critical Radiant Flux	ASTM E648	Class II
Flammability – Pill Test	ASTM D2859	Pass
Force Reduction	Deltec	11.4%
Energy Restitution	Deltec	72.20%
Vertical Deflection / Deformation	ASTM F2772	0.5mm
Surface Effect Slip Resistance	ASTM F2772	Pass
Vertical Ball Rebound	ASTM F2772	100%
Force Reduction	ASTM F2772	10%
Impact Insulation Class (IIC)	ASTM E492	53
Sound Transmission Class (STC)	ASTM E90	54
Delta IIC	ASTM E2179	22
Noise Reduction Coefficient	ASTM C423	0.05
Sheet Dimension	Manufacturer	4' wide x [X] LF/ 1.22M x [X] M
Standard Width Tolerance	Manufacturer	+3/4" -0" / +19 mm – 0mm
Standard Length Tolerance	Manufacturer	+ 1% - 0
Standard Thickness Tolerance	Manufacturer	+ 0.6 mm

Surfaces Install: Flat Hard Surface, Indoors

Shipping: Shrink wrapped on pallets, ships via freight delivery.

Greatmats.com  
117 Industrial Ave  
Milltown, WI 54858  
Toll free: 877-822-6622

Direct voice: 715-653-6100  
Fax: 715-825-4928  
info@greatmats.com  
Revised 10/2024