

GREATMATS

Performance Motivate Rubber Roll per SF Product Specifications

Roll Size:	4' wide by custom length. Minimum length 30 LF.
Roll Thickness:	7.5 mm total: 5mm Underlayment plus 2.5 mm Surface Wear Layer, +/- .6mm
Roll Weight:	1.53 lbs per sf
Standard Colors:	Blue Premium, Dark Gray Premium, Mocha Latte 2, Steel Appeal 2
Premium Colors:	Medium Grey Premium, Charcoal Premium, Dark Taupe Premium, Warm Grey Premium
Supreme Colors:	Navy Premium, Green Premium, Maroon Premium, Red Premium
Material:	High quality post-consumer recycled rubber granules encapsulated in a wear and water-resistant elastomeric network with a fusion bonded reprocessed EPDM surface wear layer.

Performance Criteria	Test Method	Typical Results
Static Load Limit	ASTM F970 @ 250 PSI	0.004"
Slip Resistance / Coefficient of Friction	ASTM D2047	>0.9
VOC's / FloorScore / CHPS / CA 01350	ASTM D5116	Pass
Resistance to Light by Color Change	ASTM F1515	Pass
Resistance to Heat by Color Change	ASTM F1514	Pass
Chemical Resistance	ASTM F925	Good
Abrasion Resistance	ASTM D3389	<1g, 1000 cycle
Flammability – Critical Radiant Flux	ASTM E648	Class II
Flammability – Pill Test	ASTM D2859	Pass
Force Reduction	Deltec	23.90%
Energy Restitution	Deltec	59.40%
Impact Insulation Class (IIC)	ASTM E492	TBD
Sound Transmission Class (STC)	ASTM E90	TBD
Delta IIC	ASTM E2179	TBD
Noise Reduction Coefficient	ASTM C423	TBD
Vertical Deflection / Deformation	ASTM F2772	1.2 mm
Surface Effect Slip Resistance	ASTM F2772	Pass
Vertical Ball Rebound	ASTM F2772	106%
Force Reduction	ASTM F2772	25%
Sheet Dimension	Manufacturer	4' wide x [x] LF / 1.22M x [X] M
Standard Width Tolerance	Manufacturer	+3/4" -0" / +19 mm – 0mm
Standard Length Tolerance	Manufacturer	+ 1% - 0
Standard Thickness Tolerance	Manufacturer	+ 0.6 mm

Surfaces Install: Flat Hard Surface, Indoors

Shipping: Shrink wrapped on pallets, ships via freight delivery.

Greatmats.com
117 Industrial Ave
Milltown, WI 54858
Toll free: 877-822-6622

Direct voice: 715-653-6100
Fax: 715-825-4928
info@greatmats.com
Revised 10/2024