

### Performance Rally Rubber Rolls Product Specifications

**Sku:** Perf-R-Roll-14.5  
**Roll Size:** 4' wide + 3/4" – 0", by custom length, + 1% - 0". Minimum length 30 LF.  
**Roll Thickness:** 14.5 mm: 12mm Underlayment plus 2.5 mm Surface Wear Layer, +/- .6mm  
**Roll Weight:** 2.34 lbs per sf  
**Colors:** Blue Premium, Dark Gray Premium, Mocha Latte, Steel Appeal  
**Material:** High quality post-consumer recycled rubber granules encapsulated in a wear and water-resistant elastomeric network with a fusion bonded reprocessed EPDM surface wear layer.

Performance Criteria	Test Method	Result
Tensile Strength	ASTM D 412	>200 PSI
Flexibility ¼" mandrel	ASTM F 137	Pass
Thermal Conductivity	ASTM C 518	>0.4"
Static Load Limit	ASTM F 970 @ 250PSI	0.009" Typical
Coefficient of Friction	ASTM D 2047	> 0.9
V.O.C. Compliant	ASTM D 5116	Yes
Color Stability	ASTM F-1515	Good
Chemical Resistance	ASTM F-925	Good
Abrasion Resistance	ASTM D 3389 / EN 649	<1g, 100 cycle
Resistance to Heat	ASTM F 1514	Δ E <8.0
Pill Test	ASTM D 2859	Pass
Vertical Deflection / Deformation	ASTM F 2772	2.66 mm
Surface Effect Slip Resistance	ASTM F 2772	Pass
Ball Rebound	ASTM F 2772	98.8%
Force Reduction	ASTM F 2772	35.7%

**Surfaces Install:** Flat Hard Surface, Indoors  
**Shipping:** Shrink wrapped on pallets, ships via freight delivery.

Greatmats.com  
 117 Industrial Ave  
 Milltown, WI 54858  
 Toll free: 877-822-6622  
 Fax: 715-825-4928  
 info@greatmats.com  
 11/2016