

Performance Rally Rubber Tiles Product Specifications

Sku: Perf-R-Tile-14.5
Roll Size: 23 inches x 23 inches. Minimum order 183 sq ft.
Roll Thickness: 14.5 mm: 12mm Underlayment plus 2.5 mm Surface Wear Layer, +/- .6mm
Roll Weight: 2.34 lbs per sf
Colors: Blue Premium, Dark Gray Premium, Mocha Latte, Steel Appeal
Material: High quality post-consumer recycled rubber granules encapsulated in a wear and water-resistant elastomeric network with a fusion bonded reprocessed EPDM surface wear layer.

Performance Criteria	Test Method	Result
Tensile Strength	ASTM D 412	>200 PSI
Flexibility ¼" mandrel	ASTM F 137	Pass
Thermal Conductivity	ASTM C 518	>0.4"
Static Load Limit	ASTM F 970 @ 250PSI	0.009" Typical
Coefficient of Friction	ASTM D 2047	> 0.9
V.O.C. Compliant	ASTM D 5116	Yes
Color Stability	ASTM F-1515	Good
Chemical Resistance	ASTM F-925	Good
Abrasion Resistance	ASTM D 3389 / EN 649	<1g, 100 cycle
Resistance to Heat	ASTM F 1514	Δ E <8.0
Pill Test	ASTM D 2859	Pass
Vertical Deflection / Deformation	ASTM F 2772	2.66 mm
Surface Effect Slip Resistance	ASTM F 2772	Pass
Ball Rebound	ASTM F 2772	98.8%
Force Reduction	ASTM F 2772	35.7%

Surfaces Install: Flat Hard Surface, Indoors
Shipping: Shrink wrapped on pallets, ships via freight delivery.

Greatmats.com
 117 Industrial Ave
 Milltown, WI 54858
 Toll free: 877-822-6622
 Fax: 715-825-4928
 info@greatmats.com
 11/2016