



Product Specifications

Product: Equi Rubber Tile

MODULE SIZE: 1 tile = 4 square feet

Width 24"

Length 24"

Thickness 1"

MODULE WEIGHT: 16.75 lbs per tile
Per Square Foot: 4.2 lbs

MATERIAL: Recycled Rubber Tires with Urethane Binding Agent
Density of Shore A 55-65 degrees

FLAME SPREAD:	ASTM E108	Class A
FLAMMABILITY:	ASTM E648	Class II
FLAMMABILITY:	ASTM 2859	Pass
TOXICITY:	ASTM D2075	Lead free
SLIP RESISTANCE:	ASTM F1677	Dry .063, Wet .052
SKID RESISTANCE:	ASTM E303	Dry 96, Wet 47
TENSILE STRENGTH:	ASTM D412	1175.3 psi
WEAR RESISTANCE:	ASTM D3884	1.64% Loss/3000c
UV RESISTANCE:	QPanelQUV	<3.0/4032ksqm

WEIGHT LOADING: Designed for human traffic and livestock

SURFACE TEXTURE: Slight granular surface texture

MODULAR DESIGN: Square with Flat Sides.
Can be installed with connector pins that fit into the tile sides, and connect the tiles laterally.

GROUND SURFACES: Designed for Installation on any Hard Flat Surface

SHIPPING: Palletized and shrink wrapped on 4x4 ft. pallets

WARRANTY: 5 Year Warranty

Greatmats.com
117 Industrial Ave
Milltown, WI 54858
V: 877-822-6622 F: 866-895-5550
info@greatmats.com
revised 6/2014