



SOF-TRED Anti-Fatigue Mat 3/8 Inch

Product Specifications

SKU: 411S03XX

- Mat Size:** 2x3 ft, 3 x 5 ft, 3x12 ft
Thickness: 3/8 inch
Mat Weight: 2x3 ft 3.18 lbs., 3x5 ft 7.95 lb., 3x12 ft 19.08 lbs.
Colors: Black, Black/Yellow, Gray
Texture: Pebble top surface design
Material: PVC/Foam
Weight Loading: Human foot traffic
Surfaces Install: Flat surface, indoor installation
Shipping: 2x3 ft - 1 piece per 6.25x6.25x25 inches box, 60 boxes per pallet
3x5 ft - 1 piece per 8 x 8 x 38 inches box, 24 boxes per pallet
3x12 ft - 1 piece per 10x10x38 inches box, 6 boxes per pallet
- Warranty:** 1 Year limited manufacturer's

Features:

PRODUCT STANDARDS		
ITEM	STANDARD	RATING
Static Coefficient of Friction	ASTM C1028-96	Dry: 80
Compression Deflection	ASTM D-575	@ 20 lbs./in ² : 0.211 in. @ 40 lbs./in ² : 0.269 in.
Durometer (Shore A)	ASTM D2240-02	15
Surface Flammability of Carpets and Rugs Ignition Characteristics - Finished Textile Floor Covering Material	CPSC FF 1-70(ASTM D-2859)	Pass
Tear Strength	ASTM D1004-94a-03	7.0 lbs.
Elongation/Tensile	ASTM D412	81.5 lbs./in ²
Abrasion Resistance (Measured in % weight loss)	ASTM D3884-01	@1000 cycles: (33.62%)

Greatmats.com
117 Industrial Ave
Milltown, WI 54858
Toll free: 877-822-6622
Fax: 715-825-4928
info@greatmats.com