



## SOF-TRED Anti-Fatigue Mat 3/8 Inch

Product Specifications

SKU: 411S03XX

- Mat Size:** 2x60 ft, 3x60 ft, 4x60 ft, 6x60 ft
- Thickness:** 3/8 inch
- Mat Weight:** 2x60 ft 63.6lbs., 3x60 ft 95.4 lbs., 4x60 ft 127.2 lbs., 6x60 ft 190.8 lbs.
- Colors:** Black, Black/Yellow, Gray
- Texture:** Pebble top surface design
- Material:** PVC/Foam
- Weight Loading:** Human foot traffic
- Surfaces Install:** Flat surface, indoor installation
- Shipping:**
  - 2x60 ft - 1 piece per 20x20x26 inches box, 6 boxes per pallet
  - 3x60 ft - 1 piece per 20x20x38 inches box, 4 boxes per pallet
  - 4x60 ft - 1 piece per 20x20x50 inches box, 4 boxes per pallet
  - 6x60 ft - 1 piece per 21.5x21.5x74 inches box, 4 boxes per pallet

**Warranty:** 1 Year limited manufacturer's

### Features:

PRODUCT STANDARDS		
ITEM	STANDARD	RATING
Static Coefficient of Friction	ASTM C1028-96	Dry: 80
Compression Deflection	ASTM D-575	@ 20 lbs./in <sup>2</sup> : 0.211 in. @ 40 lbs./in <sup>2</sup> : 0.269 in.
Durometer (Shore A)	ASTM D2240-02	15
Surface Flammability of Carpets and Rugs Ignition Characteristics - Finished Textile Floor Covering Material	CPSC FF 1-70(ASTM D-2859)	Pass
Tear Strength	ASTM D1004-94a-03	7.0 lbs.
Elongation/Tensile	ASTM D412	81.5 lbs./in <sup>2</sup>
Abrasion Resistance (Measured in % weight loss)	ASTM D3884-01	@1000 cycles: (33.62%)

Greatmats.com  
117 Industrial Ave  
Milltown, WI 54858  
Toll free: 877-822-6622  
Fax: 715-825-4928  
info@greatmats.com