



SOF-TRED Anti-Fatigue Mat 9/16 inch

Product Specifications

SKU: 411S03xx

Mat Size:	2x60 ft, 3x60 ft, 4x60 ft, 6x60 ft
Thickness:	9/16 inch
Mat Weight:	2x60 ft 111.6 lbs., 3x60 ft 167.4 lbs., 4x60 ft 223.2 lbs., 6x60 ft 334.8 lbs.
Colors:	Black, Black/Yellow, Gray
Texture:	Pebble top surface design
Material:	PVC/Foam
Weight Loading:	Human foot traffic
Surfaces Install:	Flat surface, indoor installation
Shipping:	2x60 ft - 1 piece per 22.5x22.5x26 inches box, 6 boxes per pallet 3x60 ft - 1 piece per 22.5x22.5x38 inches box, 4 boxes per pallet 4x60 ft - 1 piece per 22.5x22.5x50 inches box, 4 boxes per pallet 6x60 ft - 1 piece per 21.5x21.5x74 inches box, 4 boxes per pallet

Features:

PRODUCT STANDARDS		
ITEM	STANDARD	RATING
Static Coefficient of Friction	ASTM C1028-96	Dry: 80
Compression Deflection	ASTM D-575	@ 20 lbs./in ² : 0.211 in. @ 40 lbs./in ² : 0.269 in.
Durometer (Shore A)	ASTM D2240-02	15
Surface Flammability of Carpets and Rugs Ignition Characteristics - Finished Textile Floor Covering Material	CPSC FF 1-70(ASTM D-2859)	Pass
Tear Strength	ASTM D1004-94a-03	7.0 lbs.
Elongation/Tensile	ASTM D412	81.5 lbs./in ²
Abrasion Resistance (Measured in % weight loss)	ASTM D3884-01	@1000 cycles: (33.62%)

Greatmats.com
117 Industrial Ave
Milltown, WI 54858
Toll free: 877-822-6622
Fax: 715-825-4928
info@greatmats.com