



SuperFoam Comfort Anti-Fatigue Mat

Product Specifications

Sku: 440S00xx

Mat Size:	2x3 ft, 3x3 ft, 3x5 ft, 3x8 ft, 4x6 ft
Thickness:	3/4 inch
Mat Weight:	2x3 ft 3.78 lbs., 3x3 ft 5.67 lbs., 3x5 ft 9.45 lbs., 3x8 ft 15.12 lbs., 4x6 ft 15.12 lbs.
Colors:	Black
Surface:	Pebble top surface design
Material:	PVC/Rubber
Weight Loading:	Human foot traffic
Surfaces Install:	Lay flat
Shipping:	2x3 ft - 1 piece per 8x8x25.5 inch box, 24 boxes per pallet 3x3 ft - 1 piece per 8x8x38 inch box, 24 boxes per pallet 3x5 ft - 1 piece per 9.25 x 9.25 x 38 inch box, 20 boxes per pallet 3x8 ft - 1 piece per 10x10x38.5 inch box, 15 boxes per pallet 4x6 ft - 1 piece per 11x11x50 inch box, 9 boxes per pallet
Warranty:	3 Year limited manufacturer's

Features:

PRODUCT STANDARDS		
ITEM	STANDARD	RATING
Modified Slip Test: Avg. C.O.F. (Coefficient of Friction)	ASTM D-1894-01	VCT: 0.73, Painted Concrete: 0.73, Vinyl Flooring: 0.66, Epoxy Painted Concrete: 0.83
Compression Deflection		@ 20 lbs/in2: 0.302 @ 40 lbs/in2: 0.445
Tear Resistance (Measured in lbs.)	ASTM D-1004-94a-03	13.1 lbs.
Breaking Load & Elongation	ASTM D412	Breaking Load - 45.4 lbs/in2 Elongation - 103.04%
Abrasion Resistance	ASTM D3884	@ 500 cycles: 14.8% @ 1000 cycles: 25.7%
Critical Radiant Flux	ASTM E-648	Watts per Cm2: 0.67
Durometer (Shore A)	ASTM D-2240	10
Surface Flammability/Carpets and Rugs	ASTM D-2859/CPSC FF- 170	Pass

Greatmats.com
117 Industrial Ave
Milltown, WI 54858
Toll free: 877-822-6622
Fax: 715-825-4928
info@greatmats.com