



# SuperFoam Comfort Anti-Fatigue Mat

## Product Specifications

Sku: 440Rxxxx

<b>Mat Size:</b>	2x75 ft, 3x75 ft, 4x75 ft
<b>Thickness:</b>	3/4 inch
<b>Mat Weight:</b>	2x75 ft 94.5 lbs., 3x75 ft 141.75 lbs., 4x75 ft 189 lbs.
<b>Colors:</b>	Black
<b>Surface:</b>	Pebble top surface design
<b>Material:</b>	PVC/Rubber
<b>Weight Loading:</b>	Human foot traffic
<b>Surfaces Install:</b>	Flat surface, indoor installation
<b>Shipping:</b>	1 piece per 27x24x24 inches roll, 1 mat per pallet 1 piece per 36x27x24 inches roll, 1 mat per pallet 1 piece per 48x27x24 inches roll, 1 mat per pallet
<b>Warranty:</b>	3 Year limited manufacturer's

### Features:

PRODUCT STANDARDS		
ITEM	STANDARD	RATING
Modified Slip Test: Avg. C.O.F. (Coefficient of Friction)	ASTM D-1894-01	VCT: 0.73, Painted Concrete: 0.73, Vinyl Flooring: 0.66, Epoxy Painted Concrete: 0.83
Compression Deflection		@ 20 lbs/in2: 0.302 @ 40 lbs/in2: 0.445
Tear Resistance (Measured in lbs.)	ASTM D-1004-94a-03	13.1 lbs.
Breaking Load & Elongation	ASTM D412	Breaking Load - 45.4 lbs/in2 Elongation - 103.04%
Abrasion Resistance	ASTM D3884	@ 500 cycles: 14.8% @ 1000 cycles: 25.7%
Critical Radiant Flux	ASTM E-648	Watts per Cm2: 0.67
Durometer (Shore A)	ASTM D-2240	10
Surface Flammability/Carpets and Rugs	ASTM D-2859/CPSC FF-170	Pass

Greatmats.com  
117 Industrial Ave  
Milltown, WI 54858  
Toll free: 877-822-6622  
Fax: 715-825-4928  
info@greatmats.com