



SuperFoam Perforated Anti-Fatigue Mat

Product Specifications

Sku: T17Pxxxx

| | |
|--------------------------|--|
| Mat Size: | 3x75 ft, 4x75 ft |
| Thickness: | 5/8 inch |
| Mat Weight: | 3x75 ft 200.25 lbs., 4x75 ft 267 lbs. |
| Colors: | Black |
| Texture: | Perforated pebble top design surface |
| Material: | PVC/Foam |
| Weight Loading: | Human foot traffic |
| Surfaces Install: | Flat surface, indoor installation |
| Shipping: | 3x75 ft - 1 piece per 36x27x24 inches box, 1 box per pallet 4x75 ft – 1 piece per 48x27x24 inches box, 1 box per pallet |
| Warranty: | 3 Year limited manufacturer's |

Features:

| PRODUCT STANDARDS | | |
|--|-------------------------|------------|
| ITEM | STANDARD | RATING |
| 25% Compression Resistance (psi) | ASTM D1056 | 6.0 – 12.0 |
| 50% Compression Set (%) | ASTM D1056 | 25 max. |
| Water Absorption (lb/ft ²) | ASTM D1667 | 0.1 max. |
| Tensile Strength (psi) | ASTM D412 | 90 min. |
| Surface Flammability/Carpets and Rugs | ASTM D-2859/CPSC FF-170 | Pass |
| Elongation (%) | ASTM D412 | 100 min. |
| 0 Burn Rate | Flammability, FMVSS302 | Pass |

Greatmats.com
117 Industrial Ave
Milltown, WI 54858
Toll free: 877-822-6622
Fax: 715-825-4928
info@greatmats.com