



SuperFoam Solid Anti-Fatigue Mat

Product Specifications

Sku: T17S00xx

- Mat Size:** 2x3 ft, 3x3 ft, 3x4 ft, 3x5 ft, 3x6 ft, 3x8 ft
Thickness: 5/8 inch
Mat Weight: 2x3 ft 4.86 lbs., 3x3 ft 7.29 lbs., 3x4 ft 9.72 lbs., 3x5 ft 12.15 lb., 3x6 ft 14.58 lbs., 3x8 ft 19.44 lbs.
Colors: Black
Texture: Solid pebble top design surface
Material: PVC/Foam
Weight Loading: Human foot traffic
Surfaces Install: Flat surface, indoor installation
Shipping: 2x3 ft - 1 piece per 8x8x25.5 inch box, 24 boxes per pallet
3x3 ft - 1 piece per 8x8x38 inch box, 24 boxes per pallet
3x4 ft - 1 piece per 8x8x38 inch box, 24 boxes per pallet
3x5 ft - 1 piece per 9.25x9.25x38 inches box, 20 boxes per pallet
3x6 ft - 1 piece per 10x10x38.5 inches box, 15 boxes per pallet
3x8 ft - 1 piece per 10x10x38.5 inches box, 15 boxes per pallet
Warranty: 3 Year limited manufacturer's

Features:

PRODUCT STANDARDS		
ITEM	STANDARD	RATING
25% Compression Resistance (psi)	ASTM D1056	6.0 – 12.0
50% Compression Set (%)	ASTM D1056	25 max.
Water Absorption (lb/ft ²)	ASTM D1667	0.1 max.
Tensile Strength (psi)	ASTM D412	90 min.
Surface Flammability/Carpets and Rugs	ASTM D-2859/CPSC FF-170	Pass
Elongation (%)	ASTM D412	100 min.
0 Burn Rate	Flammability, FMVSS302	Pass

Greatmats.com
117 Industrial Ave
Milltown, WI 54858
Toll free: 877-822-6622
Fax: 715-825-4928
info@greatmats.com