

Garden Deck Tiles

Garden outdoor deck tile is made from wood and plastic composite to resist weather and insect damage. Decking tiles can be laid in two directions to create a unique pattern. The interlocking tiles are easy to lay and large areas can be installed quickly as no bearers or fixings are required. Our tiles are more eco-friendly and more durable compared to wood outdoor tiles. Simply click your floor together in just minutes with this user-friendly flooring system.

Details:

Product	Thickness	Width	Length	Weight per tile	Per box
Outdoor WPC Decking Tile	.9 inches	12 inches	12 inches	2.4 pounds	11pieces

Deck Tile Product Type	Outdoor WPC decking tile	Material	Wood Plastic Composite	
Fastener Recommendation	Simply interlock the tiles together.	Features	Prefinished, Water resistant	

Applications	Features	Benefits
Hotel Terraces	Natural wood look	Does not splinter, split or rot
Boardwalks	Low maintenance	Anti-slip qualities greater than timber and dries quick
Balcony Decking	Long lifespan	Can be jet washed when necessary
Leisure Centers	Concealed fixings	Can be sanded to remove stains
Patios	No splintering	Retains natural timber appearance with minimal maintenance
Theme Parks	UV / Color stabilized	Can be jet washed when necessary
Pool Decking	Slip resistant	Need no staining, oiling or painting
Public Areas	Mold resistant	Minimal moisture absorption
Roof Gardens and Terraces	Water resistant	Fast replacement of old tiber decking

Test Report:

Test Item	Test Method	Test result	Remark
Density	ASTM D792-13	1.33g/cm3	
Flexural Strength	ASTM D790-10	40.4MPa	
Flexural modulus	ASTM D790-10	5240MPa	
Impact Strength	ASTM D4812-11	72J/m	
hardness	ASTM D2240-05	D/72/1	
Tensile Strength	ASTM D638-14	25.5MPa	
Water Absorption	ASTM D570-98	1.15%	
Coefficient of linear thermal expansion (1/°C)	ASTM D696-08	31.85*10 ⁻ 6	-30°C-30°C:

Greatmats.com 117 Industrial Ave Milltown, WI 54858 877-822-6622

Fax: 715-825-4928 info@greatmats.com