

Matrax 4x4 HD Composite Drivable Mats

THE MOST VERSATILE MAT IN ITS CLASS.

FEATURES

- Closed-back design for full contact with the ground
- Engineered to handle thermal expansion between panels so surface stays smooth, even in extreme temperatures
- Vertical locking system with reinforced structural ribbing
- Uniform lateral load transfer between panels
- Fully driveable and pedestrian friendly
- Easy installation, handling, and transport
- 100% recyclable

APPLICATIONS

The Matrax high-performance system is designed for use on sites that require vehicular access and capacity for supporting heavy loads such as fully-loaded semi trucks, cranes and construction and equipment. Other applications include hardscape and turf protection, flooring for modular structures and safe pedestrian walkways and work platforms.



Specification	Standard	Metric
Net Working Surface	13.5 ft ²	1.25 m ²
Weight	50 lbs	22.68 kg
Compression Strength	450 psi	3,100 kps
Max Wheel Load	300 psi	2,068 kps
Max Allowable Deflection	3 in	7.62 cm
Temperature Range	-4°F – 113° F	-20°C – 45°C
Burn Rating	UL 94-HB	
Surface Texture	Diamond	

ADA compliant ramps and edge support blocks enhance the appearance, function, and protection of the mats.