



Product Specifications for Gym Floor Cover 22 oz Vinyl

WARRANTY:	10 Years pro-rated
OVERALL WEIGHT:	22 oz./sq./yd. +/- 5%
SUBSTRATE:	5 oz. woven polyester
COATING:	17 oz. PVC with approximately 50% on each side
TENSILE STRENGTH:	295 lbs. x 285 lbs. (ASTM D5034)
TEAR STRENGTH:	110 lbs. X 75 lbs. (ASTM D2261)
FLAME RESISTANCE:	Must meet these specifications: NFPA-701 Large scale, Boston Fire Marshall, Calif. Fire Marshall, UL-214, U.S. Military spec. MIL-C-20696. Testing per FED STD 191 Method #5903 for self-extinguishing characteristics.

Mildew and Odor

RESISTANCE:	Must contain fungicide and odor inhibitor equal to "Troysan" to contain bacterial growth and odor.
CONSTRUCTION:	Fabric selections to be 10 ft. wide sections or as required. Heat sealed sections to be welded with a minimum 1" wide seam that is as strong as the fabric itself.

Please note that the values above represent typical data and are subject to slight variation.

Greatmats.com
117 Industrial Ave
Milltown, WI 54858
877-822-6622
info@greatmats.com