



Gym Floor Covering Carpet Tile

Installation Instructions

SKU: PDTILE2-

Storage

Store at a moderate room temperature. Protect all materials and maintenance products from extremes of temperature during shipping. Do not stack pallets.

Note - *These instructions supersede any verbal or written instructions, and must be followed for the warranty to be in effect.*

Installation Instructions

Existing Resilient or Gym Flooring

Gym Floor Covering Carpet Tile is designed to be a durable and attractive gym floor cover in the form of easy to handle tiles. The giant-sized mats protect athletic flooring during non-sports events and activities.

Do not install over non-compatible substrates such as asphalt, any bituminous or asphalt-saturated material.

Substrates such as terrazzo, stone, ceramic tile, metal must be covered with a suitable underlayment/leveling compound following the manufacturer's written instructions. Please contact info@greatmats.com for specific recommendations for all other types of subfloors/substrates.

After substrate is prepared properly the area must also be kept free of any other trades or traffic (protect if necessary) and clean. When cleaning the substrate, use only dustless vacuum cleaners to remove all dirt and debris.

The material layout should be decided by the architect, designer or end user.

Great care is taken to properly label and inspect materials for defects at all phases of manufacturing and handling by the manufacturer. However, in the rare case where the wrong product or material with visible defects is shipped, these products must not be installed. Careful inspection of the product before installing is the responsibility of the installer. Installation of the product denotes acceptance of the product. The manufacturer will not honor any warranty complaints for materials installed in the wrong color, with visible defects or other damage.

Gym Floor Covering Carpet Tiles lie flat on top of the wood gym flooring and there are no unsightly wrinkles or ripples to cause potential tripping hazards. Easy to set up and break down, this gym floor cover doesn't require adhesive, tape or lots of special accessories. These tiles are non-staining plus the backing keeps floors clean. To minimize the chance of damage, proper glides must be used on chairs and other furniture that may side directly across the floor. They must have glides that are a minimum of 1 inch in diameter. Heavy objects such as equipment, appliances, fixtures and heavy furniture must not be moved directly across the floor. Using protective boards will reduce the chance of damage.

Direct sunlight can cause UV damage (fading or bleaching) to most interior finishes so Low E glass should be selected that will reduce the UV transmission to less than 1%. If glass without sufficient UV protection has already been installed, apply 3M protection film (or similar) on the windows to reduce the UV transmission to less than 1%. Please contact the film manufacturer for specific recommendations and application instructions.

Greatmats.com
117 Industrial Ave
Milltown, WI 54858
Toll free: 877-822-6622

Direct voice: 715-653-6100
Fax: 715-825-4928
info@greatmats.com
10/2025