



Activation Tile™ Maintenance

Maintenance Instructions - Activation Sport Tile

These instructions supersede any verbal or written instructions and must be followed in order for the warranty to be in effect.

Overall

Preventative maintenance: Because 90% of all dirt in a building comes in on footwear, the manufacturer strongly recommends installing and maintaining entrance matting (preferably permanently installed) at all outdoor entrances (20-30 linear feet for major entrances; less for infrequently used entrances). Doing this will improve indoor air quality, reduce flooring maintenance costs, and lengthen the life of your interior floors.

Safety: Always post “Wet floor” and/or “Caution” tape when wet maintenance is going to be performed. Refer to cleaners’ MSDS for any Personal Protective Equipment requirements.

Cleaning and disinfecting products: the manufacturer recommends products manufactured by Diversey Inc., which is ISO 9002 and ISO 14000 certified. In using these products, follow the instructions on the label. If you have questions about their use, contact the manufacturer directly.

Actions not to take: Activation Sport Tile does not require waxing, buffing, or stripping. Therefore, there is no need to apply any type of floor finishes or waxes. In addition,

DO NOT

- Use dust mops treated with oils or silicones.
- Use petroleum based cleaners.

Initial Cleaning

1. Sweep and/or dust mop or vacuum the floor with heavy-duty commercial vacuum to remove all dirt and grit. **This is the single most important maintenance activity for preserving the floor’s appearance and performance – and typically the most overlooked and omitted.**
2. Post “wet floor” signs.
3. Scrub the floor using a buffer or auto scrubber fitted with a soft nylon brush or purple scrub pad. The floor can also be scrubbed using a microfiber mop.
4. We recommend using appropriate pH neutral cleaners (including consideration of such specialty cleaners as Diversey Profi & Wiwax) and maintenance. Never flood the floor with water during cleaning process.

Activation Tile – Maintenance – continued

5. Use a wet vacuum to quickly pick up the soiled solution from the floor and rinse with clean water. Again, do not flood the floor.
6. Prohibit foot traffic on flooring until area is completely dry.

Routine Cleaning

1. Sweep and/or dust mop or vacuum (with heavy-duty commercial vacuum) the floor to remove all dirt and grit. **This is the single most important maintenance activity for preserving the floor's appearance and performance – and typically the most overlooked and omitted.** Post "wet floor" signs.
2. Damp mop the surface by using a microfiber mop or by using an auto scrubber fitted with a purple scrub pad. We recommend using a neutral detergent for cleaning and maintenance. Do not flood the floor with water. Use a wet vacuum to pick up the soiled solution from the floor and rinse with clean water. Promptly wet vacuum any remaining liquid from surface.
3. Prohibit foot traffic on flooring until area is completely dry.

Activation Sport tile is a registered Trademark of Matter Surfaces.

Greatmats.com
117 Industrial Ave
Milltown, WI 54858
Toll free: 877-822-6622
Direct voice: 715-653-6100
Fax: 715-825-4928
info@greatmats.com
Revised 10/2025