



Diamond Sof-Tred with Dyna-Shield Anti-Fatigue Mat 3x6 ft

Product Specifications

SKU: 419S0036

- Mat Size:** 3 x 6 foot x 1/2 inch thick
- Mat Weight:** 14.94 lb.
- Colors:** Black, Black/Yellow
- Surface:** Diamond top surface design
- Material:** PVC/Foam
- Weight Loading:** Human foot traffic
- Surfaces Install:** Flat surface, indoor installation
- Shipping:** 1 piece per 9.25 x 9.25 x 38 inch box, 24 boxes per pallet
- Warranty:** 3 Year limited manufacturer's warranty

Features:

PRODUCT STANDARDS		
ITEM	STANDARD	RATING
Coefficient of Friction	ASTM C1028-96	.68
Compression Deflection	Test specimen is subjected to varying compression load levels and the resulting deflection was measured. The greater the deflection, the better the anti-fatigue properties. (Inches)	.565 inch (40 lbs/sq. inch)
Tear Resistance	This test is designed to measure the force required to initiate tearing. The maximum stress, usually found near the outset of tearing, is recorded as the tear resistance in pounds (force)	Test Speed: 2 inch minute Avg. Tear Strength – 18.3 lbs.
Elongation	ASTM D412	128%
Abrasion Resistance	ASTM D3884-01	8.31 Grams (32.7%) (5,000 cycles)

Greatmats.com
117 Industrial Ave
Milltown, WI 54858
Toll free: 877-822-6622
Fax: 715-825-4928
info@greatmats.com