



Dura Trax Anti-Fatigue Mat 3x5 ft

Product Specifications

Sku: 490S0035

- Mat Size:** 3 x 5 foot x 9/16 inch thick
Mat Weight: 18 lb.
Colors: Black, Black/Yellow
Material Density: Shore A - 61
Texture: Diamond plate top design surface
Material: Rubber/Vinyl
Weight Loading: Human foot traffic
Surfaces Install: Flat surface, indoor installation
Shipping: 1 piece per 8 x 8 x 38 inch box, 26 boxes per pallet
Warranty: 5 Year limited manufacturer's warranty

Features:

PRODUCT STANDARDS		
ITEM	STANDARD	RATING
Static Coefficient of Friction	ASTM C-1028-96	Dry: 0.80
Compression Deflection		@ 20 lbs/in ² : 0.239 @ 40 lbs/in ² : 0.349
Tear Strength	ASTM D-1004-94a-03	40.4 lbs
Abrasion Resistance	ASTM D-3884	@ 500 cycles: 0.5% @ 1000 cycles: .09%
Surface Flammability/Carpets and Rugs	ASTM D-2859/CPSC FF-170	Pass
Critical Radiant Flux	ASTM E648-94A	Watts per CM ² : 0.80
Modified Slip Test: Avg. C.O.F. (Coefficient of Friction)	ASTM D-1894-01	VCT: 1.600 Painted Concrete: 2.000 Vinyl Flooring: 1.600 Epoxy Painted Concrete: 2.000
Delamination	ASTM D-903-98	3.5 lbs/in.

Greatmats.com
117 Industrial Ave
Milltown, WI 54858
Toll free: 877-822-6622
Fax: 715-825-4928
Info@greatmats.com