

## Saddle Trax Anti-Fatigue Mat 3x5 ft

**Product Specifications** 

Sku: 979S0035

Mat Size: 3 x 5 foot x 1 inch thick

Mat Weight: 24 lb.

Colors: Black, Black/Yellow, Gray
Texture: Diamond top surface design

Material: PVC/Foam Material Density: Shore A 80

Weight Loading: Human foot traffic

Surfaces Install: Flat surface, indoor installation

**Shipping:** 1 piece per 10x10x38.5 inch box, 15 boxes per pallet

**Warranty:** 3 year limited manufacturer's warranty

Features:

PRODUCT STANDARDS		
ITEM	STANDARD	RATING
Compression	Test specimen is subjected to varying compression load levels and the resulting deflection was measured. The greater the deflection, the better the anti-fatigue properties.	.815 inch (20 lbs/sq. inch)
Deflection	(Inches)  A neolite heel assembly with a predetermined	.668 inch (40 lbs/sq. inch)
Coefficient of Friction	load is pulled horizontally with a dynamometer to measure the force required to cause the assembly to slip.	.51
Abrasion Resistance	ASTM D3884-01	1.96 Grams (3.8%) (5,000 cycles)
Elongation	ASTM D412	72.3 lbs, 161.0% (average of 5 specimens)
Tear Strength	ASTM D1004	Test Speed: 2" minute Avg. Tear Strength - 50.9 lbs.
Critical Radiant Flux	ASTM E648-94A	.25 watts/square cm

Greatmats.com 117 Industrial Ave Milltown, WI 54858 Toll free: 877-822-6622 Fax: 715-825-4928

info@greatmats.com