



# PAVIGYM FLOORING CLEANING & MAINTENANCE MANUAL

V. 2018. This version replaces all previous versions.

## IMPORTANT!

- Only follow the instructions mentioned in this manual, and not any others which may be supplied to you.
- Please be aware that this manual is only valid for PAVIGYM flooring and markings products. There is a separate Operating and Maintenance Guide available for PRAMA products.
- Before using the floor, remove any protective coating which remains from the manufacturing process, with a post-installation cleaning. This protective coating is only for the sake of preventing damage during transport and retail.
- All the recommended products are manufactured by Diversey, our cleaning and maintenance products partner.
- Steam cleaning machines **MUST NOT** be used for cleaning PAVIGYM flooring products. High temperatures will affect the surface of the tiles and damage them.
- Should you have any questions about these cleaning products and their applications, please contact our Customer Service department:  
[support@pavigym.com](mailto:support@pavigym.com)

**[WWW.PAVIGYM.COM](http://WWW.PAVIGYM.COM)**

## FLOORING CLASIFICATION

### With Silicon Layer

This protective coating is only for the sake of preventing damage during transport and retail. Must be removed after the installation as it can be slippery at use.

The products related in this classification are:

- Endurance
- Endurance S&S
- Motion
- Performance
- Body Mind
- Tatami
- Paviplay
- Traffic

### Without Silicon Layer (sand surface)

The products related in this classification are:

- All Pavibasic CT
- Extreme/ Extreme S&S

## OBLIGATORY POST-INSTALLATION CLEANING.

*Immediately after installation and before first use of the flooring.*

### Product 1st step: Jontec Best.

1. Mix a bucket of water with Jontec Best. The proportion should be 100ml Jontec Best for every 1L of water.
2. Apply the solution on the floor using a broom with microfiber mop or a scrubber drier (see recommended material below).
3. Allow the solution to act for 20 min without allowing it to dry.
4. **IMPORTANT:** Rinse well with clean water and a microfiber mop or a scrubber drier as many times as necessary to ensure the elimination of the protective coating layer. If this is not done, the surface may be slippery.
5. Leave to dry completely.



## Product 2nd Step: Jontec Tensol

1. Mix a bucket of water with Jontec Tensol. The proportion should be 100ml Jontec Tensol for every 1L of water.
2. Apply the solution on the floor using a clean mop or a scrubber drier.
3. Leave to dry completely.



**Difficult stains after post-installation cleaning:** If from the result from works after the post-installation cleaning there are specific or difficult stains to remove it is recommended to use Dr. Schnell Milizid, which is an acid cleaner.

1. Mix a bucket of water with Milizid. Proportion should be 25 ml for every 1L of water.
2. Apply the solution on the difficult stain using a clean mop or a handbrush.
3. Leave the solution to take effect for 5 minutes.
4. Rinse with clean water as many times as necessary to ensure the elimination of all dirt.

## MAINTENANCE CLEANING.

*For daily use.*

**Product: Jontec Tensol.**



1. Mix a bucket of water with Jontec Tensol. The proportion should be 25ml Jontec Tensol for every 1L of water.
2. Scrub the surface with the solution using a microfiber mop or use a scrubber drier (see recommended material below).
3. Leave to dry completely.

## DEEP CLEANING.

*For intensive cleaning (should be performed between a minimum of twice and a maximum of ten times per year).*

**Product: Jontec Forward.**

1. Mix a bucket of water with Jontec Forward. The proportion should be 50ml Jontec Forward for every 1L of water.
2. Apply the solution on the floor using a microfiber mope or a scrubber drier.
3. **IMPORTANT:** Allow the solution to act for 5 minutes without allowing it to dry. An incorrect mixture concentration could cause damage to the surface after drying.
4. Scrub the solution on the floor using a broom with medium strength bristles, a microfiber mop or a scrubber drier (see recommended material below), and remove the dirty water using a mop or liquid vacuum cleaner.
5. Rinse with clean water as many times as necessary to ensure the elimination of all dirt.
6. Leave to dry completely.



## **Static Dissipative Cleaning**

Product: ELECSTAT-112

Sometimes PAVIGYM EVA products TATAMI, PAVIPLAY, BODY MIND can be charged by static electricity as it is in contact with rubber shoes sole. This can be avoided by the use of a dissipative cleaner as ELECSTAT-112.

### Application

Dilute 100 to gr of ELECSTAT-112 in 1 liter of water, preferably hot water. Use the solution either for manual or mechanical cleaning.

## **PAVIGYM Slide Cleaning**

PAVIGYM recommends the use of a window cleaner to clean the Slide tiles.

Apply the cleaner in the slide, then clean with a microfiber mop or cloth with no additional water.

After it dries, wax provided with Slide accessories can be applied to keep a slippery surface.

## SELECTIVE CLEANING.

*Stubborn dirt, specific stains...*

**Product: Sprint Performer or Sprint Spitfire**

Apply the product to a cloth, and scrub the surface until all stains have been eliminated. Wipe clean.

In case of **tough stains**:

1. Spray the product directly on to the stain.
2. Allow to act for approx 5 mins.
3. Scrub and wipe clean.



## RECOMMENDED MATERIALS.

### Disc:

[Taski ergodisc 175 & 200](#)

### Scrubber driers:

[Taski swingo 350B](#)

[Taski Swingo 455B & 455 E](#)

[Taski Swingo 755B & 755 E](#)

### Brushes and Pads\*:

[White contact pads & Microfibre mop.](#)

\*Only use white pads!

## PAVIGYM CORPORATION

t. +34 965 675 070 / f. +34 965 666 793

Ptda. Canastell I-98 E-03690 - San Vicente del Raspeig (Alicante) SPAIN