



PRODUCT DATA SHEET: FIRMAGRIP

SIZES & WEIGHTS

<i>All dimensions are nominal</i>	Height (in)	Length (ft)	Widths (ft)			Weight (lbs/sq.ft)
<i>Tolerances</i>	+/- 0.05"	0+1.0'	+/- 1/2"			
Firmagrip	9/16"	33'	2'	3'	4'	2.14



GENERAL

Appearances	Open grid “heel proof” design diamond cut surface.
Colors	Available in homogenous standard colors; Green, Red and Black Red color is not colorfast in direct sunlight.
Durability	One piece welded construction for maintenance free life.
Workability	Available in rolls for ease of installation. Easy to cut to size and shape. Supplied in rolls with top ribs facing outwards. Requires inverting once rolled out prior to use.
Uses	All locations, both indoor and outdoor.

Technical Data

Acoustic	Excellent sound absorption properties.
Chemical	Resistant to most acids, alkaline and oils. For specific chemical resistances, see http://www.plastexmatting.com/uploads/4/4/0/0/44003899/pvc-chemical-resistance.pdf
Composition	Flexible Polyvinyl Chloride (PVC).
Environment	It had been determined under the guidelines for the State of California Safe Drinking Water and Toxic Enforcement Act of 1986 (Prop 65), that no warning labels or information provisions are required for Firmagrip.


Black color is made from post-industrial recycled PVC, always with a minimum content of 30% up to 100%.

Plastex does not use substances currently included in the SVHC (Substances of Very High Concern) list under R.E.A.C.H.* in any matting products.

*Registration, Evaluation, Authorization, and Restriction of Chemical substances

Hygiene	Non-porous 100% Virgin PVC – Inhibits the growth of bacteria.
Reversion	Thermoplastic shrinkage can result in size reduction up to 2%. Accelerated in hot environments, refer to http://www.plastexmatting.com/uploads/4/4/0/0/44003899/vinyl-matting-dimensional-stability.pdf
Slip Resistance	DIN 51130: R11, V10
Thermal	Functional -9°F + 140°F (Slight size variation may occur at temperature extremes).
UV Light	Resistant to PVC degradation; unicolored PVC material – BSEN 607 = Delta E 1.02.
Warranty	4 years. See http://www.plastexmatting.com/uploads/4/4/0/0/44003899/warranty.pdf


ANCILLARIES



2 1/2" PVC edging strip
Supplied in rolls of 33' (10.1m) length with cold welding paste.
Colors: Black, Dark Gray




Snap Track
2 part snap track can be welded to join rolls end to end or side to side for large area covering. Supplied with welding paste.
Color: Dark Gray



3 3/4" PVC edging strip
Supplied in rolls of 33' (10.1m) length with cold welding paste.
Colors: Black, Dark Gray, Yellow



Connector clips - Side to side
For joining sections of matting together side to side. Supplied in packs of 10.



1 13/16" Aluminum edging strip
Supplied in sections of 6'6" (2m) length with fixing screws and plugs.
Color: Anodized Aluminum

Greatmats Specialty Flooring
117 Industrial Ave
Milltown, WI 54858
info@greatmats.com
877-822-6622
f: 715-825-4928
www.greatmats.com