



## PRODUCT DATA SHEET: HERONGRIPA

### SIZES & WEIGHTS

	All dimensions are nominal		Height (mm)	Lengths (m)	Widths (cm)		Weight (kg/m <sup>2</sup> )
	Tolerances (mm)		+/- 0.5	0+0.3	+/- 1		
Herongripa			15	5 & 10	60	91 122	4.3



### GENERAL

- Appearances** Open grid "duckboard" design with textured surface.
- Colors** Available in one homogeneous color; terra cotta.
- Durability** One piece welded construction for maintenance free life.
- Workability** Flexible construction is easy to cut and shape in site. Supplied in rolls with top ribs facing outwards. Requiring inverting once rolled out prior to use.
- Uses** For food processing areas.

### TECHNICAL DATA

- Acoustic** Excellent sound absorption properties.
- Chemical** Resistant to most acids, alkalines, and oils. For specific chemical resistances, see <http://www.plastexmatting.com/uploads/4/4/0/0/44003899/pvc-chemical-resistance.pdf>

- Composition** Flexible DINP plasticized Polyvinyl Chloride (PVC).
- Environment** Made from post-industrial recycled PVC, always with a minimum content of 30% up to 100%. Plastex does not use any substance currently included in the SVHC (Substances of Very High Concern) list under \*R.E.A.C.H in any matting products. \* **Registration, Evaluation, Authorization and Restriction of Chemical substances**

**Hygiene**                    Non-porous 100% virgin PVC – Inhibits the growth of bacteria.  
 Anti-bacterial SteriTouch additive; Test JIS Z 2801:2000 – Determination of the  
 antibacterial effect against:  
 Staphylococcus Aureus                    Result - Antimicrobial pass of >99%  
 E. Cloi    Result – Antimicrobial pass of 99%  
 Anti-fungal SteriTouch additive; Test method ASTM G21-09 – Determining  
 resistance to fungi.    Result – Nil growth after 4 weeks

**Reversion**                    Thermoplastic shrinkage can result in size reductions up to 2%.  
 Accelerated in hot environments. Refer to  
<http://www.plastexmatting.com/uploads/4/4/0/0/44003899/vinyl-matting-dimensional-stability.pdf>

**Slip Resistance**            ASTM F 1677 – Dry/Wet: 0.8/0.7  
 DIN 51130:    R11, V10

**Thermal**                        Functional -9.4°F to 140°F

**UV Light**                      Resistant to PVC degradation.

**Warranty**                      2 years. See  
<http://www.plastexmatting.com/uploads/4/4/0/0/44003899/warranty.pdf>

**Greatmats.com**  
**117 Industrial Ave - Milltown, WI 54858**  
**info@greatmats.com**