



## PRODUCT DATA SHEET: HERONAIR

### SIZES & WEIGHTS

<i>All dimensions are nominal</i>	Height (mm)	Lengths (m)	Widths (cm)		Weight (kg/m <sup>2</sup> )
<i>Tolerances (mm)</i>	<i>+/- 0.5</i>	<i>0+0.3</i>	<i>+/- 1</i>		
Heronair	10	10	50	75 100	4.5



### GENERAL

Appearances	Open grid “duckboard” design with textured surface.
Colors	Available in homogeneous standard colors, Black.
Durability	One piece welded construction for maintenance free life.
Workability	Flexible construction is easy to cut and shape on site. Supplied in rolls with top ribs facing outwards. Requires inverting once rolled out prior to use.
Uses	All medium indoor and outdoor locations.

### TECHNICAL DATA

Acoustic	Excellent sound absorption properties.
Chemical	Resistant to most acids, alkalines, and oils. For specific chemical resistances, see <a href="http://www.plastexmatting.com/uploads/4/4/0/0/44003899/pvc-chemical-resistance.pdf">http://www.plastexmatting.com/uploads/4/4/0/0/44003899/pvc-chemical-resistance.pdf</a>
Composition	Flexible DINP plasticized Polyvinyl Chloride (PVC).
Environment	Made from post-industrial recycled PVC, always with a minimum content of 30% up to 100%. Plastex does not use any substance currently included in the SVHC (Substances of Very High Concern) list under *R.E.A.C.H in any matting products. * <i>Registration, Evaluation, Authorization and Restriction of Chemical substances</i>

Fire	DIN 4102 Part 1 – Classification B2	
Hygiene	Non-porous 100% virgin PVC – Inhibits the growth of bacteria.	
Reversion	Thermoplastic shrinkage can result in size reductions up to 2%. Accelerated in hot environments. Refer to, <a href="http://www.plastexmatting.com/uploads/4/4/0/0/44003899/vinyl-matting-dimensional-stability.pdf">http://www.plastexmatting.com/uploads/4/4/0/0/44003899/vinyl-matting-dimensional-stability.pdf</a>	
Slip Resistance	ASTM F 1677 – Dry/Wet: DIN 51130:	0.6/0.6 R11/V10
Thermal	Functional -9.4° F to 140° F ( Slight variations may occur in extreme temperature changes)	
UV Light	Resistant to PVC degradation.	
Warranty	2 years. See <a href="http://www.plastexmatting.com/uploads/4/4/0/0/44003899/warranty.pdf">http://www.plastexmatting.com/uploads/4/4/0/0/44003899/warranty.pdf</a>	

**Greatmats.com**  
**117 Industrial Ave**  
**Milltown, WI 54858**  
[\*\*info@greatmats.com\*\*](mailto:info@greatmats.com)  
**877-822-6622**  
**F: 715-825-4928**