

BOUNCE BACK PLAYGROUND TILES SPECIFICATIONS

MATERIAL:	100% Recycled Tire Rubber	
SIZE:	24" x 24" Tiles	
SURFACE:	Porous, added traction top surface.	
UNDER SURFACE:	Waffle patterned, easy drain under surface.	
THICKNESSES:	1.75", 2.25", 2.5", 3.5", and 4".	
FALL HEIGHTS:	1.75" = 3' fall height 2.25" = 4-5' fall height 2.5" = 6' fall height 3.5" = 7-8' fall height 4" = 9-10' fall height IPEMA Certified	
TILE WEIGHTS:	1.75" = 24 lbs 2.25" = 25 lbs 2.5" = 26 lbs 3.5" = 36 lbs 4" = 40 lbs	
ORIGIN:	Manufactured entirely within the USA	
WARRANTY:	10 Year Manufacturer's warranty	
COEFFICIENT OF FRICTION:	ASTM C 1028	0.65 dry, 0.63 wet
WATER PERMEABILITY:		0.27 gal/min/sq. yd.
LEAD CONTENT:	ASTM D 4004	5.97 ppm
ABRASION RESISTANCE:	ASTM D 4060	Wear Index 657- avg.
TEAR STRENGTH:	ASTM D 624	124 lbf/in & psi avg.
DUAL DUROMETER:		25/45 resistance
WEATHERIZATION TEST:	ASTM C67 & D576	No signs of failure after freeze-thaw and
FALL HEIGHT CRITERIA	ASTM F 1292-99	Met respective design fall height criteria.

24" x 24" vibrant color tiles available in a variety of standard and EPDM colors.

Bounce Back Playground Safety Tiles meet the Consumer Product Safety Commission (CPSC) and American with Disability Act (ADA) requirements tested by the American Society for Testing and Material (ASTM) methods. All Bounce Back tiles meet the Head Injury Criteria (HIC) tests for applicable fall heights and are certified by the International Play Equipment Manufacturers Association (IPEMA)

Greatmats.com
117 Industrial Ave
Milltown, WI 54858
Toll Free: 877-822-6622
info@greatmats.com
revised 2/2017