



Silent-Tread™ Specifications

Composition: Recycled scrap tire rubber granules bonded with Polymer Binding Agent

Recycled Content: 90% Total Post Consumer, 100% Rubber from reclaimed tires

Thickness: 3.2 mm (standard), also in 2 mm, 6.4 mm and 9.5 mm

Lengths: 25, 50, and 75-foot increment standard continuous rolls

Widths: 48" Standard, custom up to 60"

Appearance: Black in color, flat surface top and bottom.

		<u>Premium</u>	<u>Soft</u>
Density:	ASTM D-3676	60 lbs/ft ³	47 lbs/ft ³
Elongation at Break:	ASTM D-412	75%	75%
Tear:	ASTM D-624	80 pli	42 pli
Hardness (Shore A):	ASTM D-2240	60	42

Roll Weight and Rolls per Pallet Soft Product:

<u>Thickness</u>	<u>Length</u>	<u>Wt. Per Roll</u>	<u>Rolls Per Pallet</u>
2mm	25ft	29 lbs	24
3.2mm	25ft	50 lbs	20
6.4mm	25ft	100 lbs	12
9.5mm	25ft	150 lbs	11

Premium Product:

<u>Thickness</u>	<u>Length</u>	<u>Wt. Per Roll</u>	<u>Rolls Per Pallet</u>
2mm	25ft	41 lbs	24
3.2mm	25ft	65 lbs	20
6.4mm	25ft	127 lbs	12
9.5mm	25ft	192 lbs	11

Greatmats.com
 117 Industrial Ave
 Milltown, WI 54858
 V: 877-822-6622
 F: 866-895-5550
 info@greatmats.com
 revised 6/2014