



DunkStar BaseCourt and Pickleball Outdoor Court Tiles Concrete Installation Specifications

For Basketball and Multi-Game Courts with Dunkstar Suspended Surfacing

- 4" Minimum compactable base material to grade
- Concrete pad 4" thick with 6" thickened edge
- 3000 psi mix
- Light broom finish
- Steel reinforcement $\frac{3}{8}$ " steel rebar 24" - 36" on center
- Slope/crown $\frac{1}{2}$ " - 1" per 16' ($\frac{1}{4}\%$ - $\frac{1}{2}\%$ slope)
- Saw cut expansion joints between 12' and 15' squares
- Expansive or unstable soil, water and climate conditions may require engineered specifications for a specific site
- Tennis court specifications for single or multiple courts are custom engineered and may require post tension concrete depending on soil, water, and climate condition
- All support posts and sleeves for basketball pole, lights, and net posts should be set in concrete pad at time of pour. If court is less than 28' wide, sleeves should be put in a 2' x 2' concrete wing

DunkStar is a registered trademark of SnapLock Industries.

Greatmats.com
117 Industrial Ave
Milltown, WI 54858
Toll free: 877-822-6622
Direct voice: 715-653-6100
Fax: 715-825-4928
info@greatmats.com
Revised 9/2025