

Product Specifications
Sterling Athletic Sound Rubber Tile

Tile Size: 24 inches x 24 inches
 Tile Thickness: Available in 2 inch or 2.75 inch thicknesses
 Tile Weight: 2 inch: 24 pounds, 2.75 inch: 29 pounds per tile
 Material: 100 % post-consumer recycled materials, Shore A Durometer 60
 Surfaces Install: Flat, hard indoor surface installations
 Shipping: Ships via freight, shrink wrapped on pallets
 Warranty: Limited Lifetime Warranty

Test Description	ASTM Ref.	Results	Test Lab	Test Date
Freeze/Thaw	C67	No deterioration	SGS	Dec 1998
Rubber Deterioration/Air Oven	D573	No deterioration	SGS	Dec 1998
Slip Resistance	E303	Dry 102 / Wet 62	SGS	Sept 1998
Slip Resistance	D2047	Dry 0.81 / Wet 0.82	SGS	Feb 1999
Compression Deflection	D1667	29.5 PSI to 25% Compression	NWL	Jan 1995
Compression Set	D395	4.37% Permanent Set	NWL	Jan 1995
Tensile Strength	D412	107 PSI	SGS	Feb 1999
Elongation at Break	D412	165%	SGS	Feb 1999
Tear Strength	D624	33.1 Lbs/Inch	SGS	Feb 1999
Wear Surface Density (Durability)	>60 lbs/Cu Ft			

Tiles are manufactured to a dimension of 24" x 24" and compressed during installation to a dimension of 23-15/16" x 23-15/16".

Greatmats.com
 117 Industrial Ave
 Milltown, WI 54858
 877-822-6622
 Fax: 715-825-4928
 info@greatmats.com
 12/2016