

Sterling Rubber Tile

TECHNICAL SPECIFICATIONS

PHYSICAL DIMENSIONS

Size	Thickness	Weight (lbs.) Ea. (Not less than...)		SofRAMP Length
		Plus		
24" x 24"	1.25"	19.30		47.75"

PHYSICAL PROPERTIES

Test Description	ASTM Ref.	Results	Test Lab	Test Date
Acoustical A09-009	EC423/E795	SAA = 0.14, NRC = 0.15	RAL	0109
Acoustical TL08-363	E90/E413	STC = 53	RAL	1208
Acoustical IN08-050	E492/E989	IIC = 59	RAL	1208
Acoustical IFC09-002	E2179	Delta IIC 26 IICc 54	RAL	0109
Freeze Thaw	C67	No deterioration	SGS	1298
Rubber Deterioration/Air Oven	D573	No deterioration	SGS	1298
Slip Resistance	E303	Dry 102 Wet 62	SGS	0998
Slip Resistance	D2047	Dry .81 Wet .82	SGS	0299
Compression Deflection	D1667	29.5 PSI to 25% Compression	NWL	0195
Compression Set	D395	4.37% Permanent Set	NWL	0195
Tensile Strength	D412	107 PSI	SGS	0299
Elongation at Break	D412	165%	SGS	0299
Tear Strength	D624	33.1 Lbs/Inch	SGS	0299
Wear Surface Density (Durability)		>60 Lbs/CuFt		
Flammability - Burning Pill Test	D2859	Pass	NWL	0195

PACKAGING INFORMATION

DuraFLEX Description	Thickness	Pieces Per Pallet	Pallet Weight	Pallet Height	Other Packaging Information
PLUS	1.25"	100	1930 Lbs.	50"	Standard Pallet Size - 50"x50" Standard Pallets in 48" Van = 19

FIVE YEAR LIMITED WARRANTY

Materials & Workmanship

